# PRODUCT LIST



A. Led Light Bar 2 - 6	Click to Get There
A1. 3W Double Row Led Light Bar ····· 2 - 3	Click to Get There
A2. 10W Single/Double Row Led Light Bar ······ 4 - 5	Click to Get There
A3. 4D/3D Lens Led Light Bar ····· 5 - 6	Click to Get There
A4. 5W Single Row Led Light Bar ····· 6 - 6	Click to Get There
A5. 3W Quad Row Led Light Bar ····· 6 - 6	Click to Get There
B. Led Work/Driving Lamp 7 - 25	Click to Get There
B1. HOT/NEW LED Driving Lamps 7 - 8	Click to Get There
B2. Led Truck Headlights ····· 8 - 10	Click to Get There
B3. Led Pod Lights 11 - 13	Click to Get There
B4. 15W/18W/27W/48W Led Work Lights 13 - 16	Click to Get There
B5. Led Work Lamps for Motor and Forklift 17 - 19	Click to Get There
B6. Led Marine Work Lights ······ 19 - 20	Click to Get There
B7. Jeep Headlight and Fog Light 22 - 22	Click to Get There
B8. High Power and Tough Led Lights 23 - 25	Click to Get There
C. LED Warning & Signal Lights 26 - 26	Click to Get There
D. Mounting Brackets for Lights 27 - 33	Click to Get There
E. Wiring Kits & DT Connectors 34 - 35	Click to Get There

Guangzhou Juntu Auto Accessories Co., Ltd.

3/F, Building 5, #63 Huangbian North Road, Baiyun District, Guangzhou, China

Website: www.juntu-auto.com

in S 8+ O P

Contact: Mike Zheng

Skype: Sales7-mike

WhatsApp: +8615899973510

Email: Sales7@juntu-auto.com



# Juntu See Guangzhou Juntu Auto Accessories Co., Ltd.

Contact: Mike Zheng Email: sales7@juntu-auto.com Mob/Whatsapp: +8615899973510

Skype: Sales7-mike Facebook/Wechat: mike652638 Website: www.juntu-auto.com

## **Product List for LED Light Bars**

Serial No.	Picture for Reference Contact Mike for More Pictures	Specification	Length (inch)	Power (W)	PCs /CTN (MOQ)	Get Price Via Email Inquiry
		D 0 ' 1 0 //El 1/G 1	7.5 inch	36W	6pcs	Get Price
JT-2600C	( takata	Beam Optional: Spot/Flood/Combo LED Chip: 3W CREE	13.5 inch	72W	6pcs	Get Price
		Effective Lumen: 70LM/W Working Voltage: 10-30V DC	21.5 inch	120W	6pcs	Get Price
Straight		Housing: Die-cast Aluminum	31.5 inch	180W	4pcs	Get Price
CREE		Mounting: Alu Firm Bracket IP Rating: IP68	41.5 inch	240W	4pcs	Get Price
Chips		Life-span: 50,000 Hours Product Warranty: 1 Year	50 inch	288W	4pcs	Get Price
нот		110ddct warranty. 1 Tear	52 inch	300W	4pcs	Get Price
			7.5 inch	36W	6pcs	Get Price
JT- 26000		Beam Optional: Spot/Flood/Combo LED Chip: 3W Osram	13.5 inch	72W	6pcs	Get Price
2000		Effective Lumen:60LM/W Working Voltage: 10-30V DC	21.5 inch	120W	6pcs	Get Price
Straight	La constitution of the	Housing: Die-cast Aluminum	31.5 inch	180W	4pcs	Get Price
Osram		Mounting: Alu Firm Bracket IP Rating: IP68 Life-span: 50,000 Hours Product Warranty: 1 Year	41.5 inch	240W	4pcs	Get Price
Chips	7		50 inch	288W	4pcs	Get Price
		Floduct Wallality. 1 Teal	52 inch	300W	4pcs	Get Price
			13.5 inch	72W	6pcs	Get Price
JT-2700C	* None	Beam Optional: Spot/Flood/Combo LED Chip: 3W CREE	21.5 inch	120W	6pcs	Get Price
	THE PERSON NAMED IN	Effective Lumen: 70LM/W Working Voltage: 10-30V DC	31.5 inch	180W	4pcs	Get Price
Curved	160	Housing: Die-cast Aluminum	41.5 inch	240W	4pcs	Get Price
CREE		Mounting: Alu Firm Bracket IP Rating: IP68	50 inch	288W	4pcs	Get Price
Chips		Life-span: 50,000 Hours	51 inch 52 inch	300W 312W	4pcs 4pcs	Get Price Get Price
нот	al .	Product Warranty: 1 Year	55 inch	348W	4pcs	Get Price
1101			13.5 inch	72W	6pcs	Get Price
JT-2700E		Beam Optional: Spot/Flood/Combo LED Chip: 3W Epsitar	21.5 inch	120W	6pcs	Get Price
		Effective Lumen: 68LM/W	31.5 inch	180W	4pcs	Get Price
Curved		Working Voltage: 10-30V DC Housing: Die-cast Aluminum	41.5 inch	240W	4pcs	Get Price
		Mounting: Alu Firm Bracket IP Rating: IP68	50 inch	288W	4pcs	Get Price
Epistar Chips	Man	Life-span: 50,000 Hours	51 inch	300W	4pcs	Get Price
		Product Warranty: 1 Year	52 inch	312W	4pcs	Get Price
		Page 2 of 35			. P. 2.3	

Deam Optional: Spot/Flood/Combo   LED Chip: 3W Osram   Effective Lumen: 60LM/W   Working Voltage: 10-30V DC   Housing: Die-cast Aluminum   Mounting: Alu Firm Bracket   IP Rating: IP68   Life-span: 50,000 Hours   Product Warranty: 1 Year   Side Brackets   Beam Optional: Spot/Flood/Combo   LED Chip: 3W CREE   Effective Lumen: 70LM/W   Working Voltage: 9-32V DC   Housing: Die-cast Aluminum   Mounting: Stainless Steel   IP Rating: IP68   Life-span: 50,000 Hours   12.5 inch   120W   6pcs   41.5 inch   240W   4pcs   4pcs   50 inch   288W   4pcs   4pcs   52 inch   312W   4pcs   4pc	Get Price
LED Chip: 3W Osram   Effective Lumen: 60LM/W   Working Voltage: 10-30V DC   Housing: Die-cast Aluminum   Mounting: Alu Firm Bracket   IP Rating: IP68   Life-span: 50,000 Hours   Product Warranty: 1 Year   Side Brackets   Beam Optional: Spot/Flood/Combo   LED Chip: 3W CREE   Effective Lumen: 70LM/W   Working Voltage: 9-32V DC   Housing: Die-cast Aluminum   Mounting: Stainless Steel   IP Rating: IP68   Life span: 50 000 Hours   12 inch   120W   6pcs   4pcs   31.5 inch   180W   4pcs   4pcs   50 inch   288W   4pcs   51 inch   300W   4pcs   52 inch   312W   4pcs   4	Get Price
Curved   Curved   Curved   Curved   Osram   Chips	Get Price
Housing: Die-cast Aluminum   Mounting: Alu Firm Bracket   IP Rating: IP68   Life-span: 50,000 Hours   Product Warranty: 1 Year   Side Brackets   Effective Lumen: 70LM/W   Working Voltage: 9-32V DC   Housing: Die-cast Aluminum   Mounting: Stainless Steel   IP Rating: IP68   Life span: 50,000 Hours   Side Brackets   Beam Optional: Spot/Flood/Combo   LED Chip: 3W CREE   Effective Lumen: 70LM/W   Working Voltage: 9-32V DC   Housing: Die-cast Aluminum   Mounting: Stainless Steel   IP Rating: IP68   Life span: 50,000 Hours   Life span:	Get Price
P Rating: IP68   Life-span: 50,000 Hours   Product Warranty: 1 Year   S1 inch   300W   4pcs	Get Price
Life-span: 50,000 Hours   Froduct Warranty: 1 Year   S1 inch   300W   4pcs   4pcs   4pcs   52 inch   312W   4pcs   4pcs   4pcs   4pcs   52 inch   312W   4pcs   4	Get Price
Side Brackets Beam Optional: Spot/Flood/Combo LED Chip: 3W CREE Effective Lumen: 70LM/W Working Voltage: 9-32V DC Housing: Die-cast Aluminum Mounting: Stainless Steel IP Rating: IP68 Life spen; 50 000 Hours    52 inch   312W   4pcs     3.9 inch   18W   18pcs     6.6 inch   36W   12pcs     9.2 inch   54W   12pcs     12 inch   72W   12pcs     12 inch   72W   12pcs     14.5 inch   90W   6pcs     17.2 inch   108W   6pcs     19.9 inch   126W   6pcs     22.6 inch   144W   6pcs     28 inch   180W   6pcs     3.9 inch   18W   18pcs     6.6 inch   36W   12pcs     12 inch   72W   12pcs     12 inch   72W   12pcs     13 inch   180W   6pcs     14 inch   72W   12pcs     15 inch   72W   12pcs     15 inch   72W   12pcs     16 inch   72W   12pcs     17 inch   108W   6pcs     18 inch   18 inch   18 inch     18 inch   18 inch	Get Price
Straight CREE  2 Kinds of Point Poin	Get Price Get Price Get Price Get Price Get Price Get Price
Straight CREE  2 Kinds of  P. 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Get Price Get Price Get Price Get Price
Straight CREE  2 Kinds of  P. J.	Get Price Get Price Get Price
Straight CREE  2 Kinds of  P. J.	Get Price Get Price
Straight CREE  Working Voltage: 9-32V DC Housing: Die-cast Aluminum Mounting: Stainless Steel IP Rating: IP68 Life span: 50,000 Hours  14.5 inch 90W 6pcs 17.2 inch 108W 6pcs 19.9 inch 126W 6pcs 22.6 inch 144W 6pcs 28 inch 180W 6pcs	Get Price
CREE  Housing: Die-cast Aluminum Mounting: Stainless Steel  IP Rating: IP68  Life graps: 50,000 Hours  17.2 inch   108W   6pcs   19.9 inch   126W   6pcs   22.6 inch   144W   6pcs   28 inch   180W   6pcs	
2 Kinds of IP Rating: IP68 Life span: 50,000 Hours  Mounting: Stainless Steel 22.6 inch   126W   6pcs   22.6 inch   144W   6pcs   28 inch   180W   6pcs	
2 Kinds of IP Rating: IP68 28 inch 180W 6pcs 28 inch 180W 6pcs	Get Price
Life copp. 50 000 Hours	Get Price
1 DIAUNUS 1 1 25 0 inch 1 22 MW 1 Zagg	Get Price
Droduct Womenty 1 Voc	Get Price
HOT 41.5 Heri 270W 4pcs	Get Price
49.4 inch   324W   4pcs	Get Price
4 inch 18W 20pcs	Get Price Get Price
JT-1200 Beam Optional: Spot/Flood/Combo 7 inch 36W 12pcs	Get Price
LED Chip: 3W CREE 10 inch 54W 12pcs	Get Price
Effective Lumen: 70LM/W Washing Walking Walking 22W DC  13.5 inch 72W 12pcs 17 inch 90W 12pcs	Get Price
Working Voltage: 9-32V DC	Get Price
Suaight Housing: Die-cast Aluminum	Get Price
Mounting: Stainless Steel    Stainless Steel   23 inch   126W   6pcs   6	Get Price
CREE IP Rating: IP68 20 inch 180W 6pcs 32 inch 180W 6pcs	Get Price
Life-span: 50,000 Hours 41 inch 234W 4pcs	Get Price
Product Warranty: 1 Year 47 inch 270W 4pcs	Get Price
50 inch 288W 4pcs	Get Price
10.4 inch 56W 12pcs	Get Price
JT-1300 Beam Optional: Combo 13.5 inch 76W 12pcs	Get Price
LED Chip: 10W CREE+3W CREE  Effective Lumen: 70LM/W  19.6 inch 116W 6pcs	Get Price
10W Working Voltage: 9-32V DC 22.7 inch 132W 6pcs	Get Price
+ Housing: Die-cast Aluminum 25.8 inch 152W 6pcs	Get Price
Mounting: Alu Firm Bracket  31.9 inch 192W 6pcs	Get Price
CREE  IP Rating: IP68 Life-span: 50,000 Hours  41.1 inch 248W 4pcs	Get Price
Product Warranty: 1 Year 47.2 inch 284W 4pcs	Get Price
50.3 inch 304W 4pcs	Get Price
4.6 inch 20W 20pcs	Get Price
Beam Optional: Spot/Flood/Combo/Euro LED Chip: 10W CREE  7.8 inch 40W 10pcs	Get Price
Effective Lumen: 86LM/W 10.9 inch 60W 10pcs	Get Price
10W Working Voltage: 9-60V DC 17.2 inch 100W 6pcs	Get Price
CREE Housing: Die-cast Aluminum 20.3 inch 120W 6pcs	Get Price
Mounting: Alu Firm Bracket  IP Rating: IP68  29.7 inch 180W 6pcs	Get Price
Life-span: 50,000 Hours 39.1 inch 240W 4pcs	Get Price
Classic Product Warranty: 1 Year 42.2 inch 260W 4pcs	Get Price
50 inch   300W   2pcs	Get Price

JT-D10-		Beam Optional: Spot/Flood/Combo/Euro	4.6 inch	40W	12pcs	Get Price
A		LED Chip: 10W CREE Effective Lumen: 86LM/W	7.8 inch	80W	6pcs	Get Price
10W CREE		Working Voltage: 9-60V DC Housing: Die-cast Aluminum Mounting: Alu Firm Bracket	10.9 inch	120W	6pcs	Get Price
Straight		IP Rating: IP68 Life-span: 50,000 Hours	17.2 inch	200W	4pcs	Get Price
Classic		Product Warranty: 1 Year	20.3 inch	240W	4pcs	Get Price
			4 inch	30W	12pcs	Get Price
JT-3200		Beam Optional: Spot/Flood/Combo	10 inch	60W	6pcs	Get Price
	or and the second	LED Chip: 10W CREE Effective Lumen: 86LM/W	16 inch	90W	6pcs	Get Price
Straight	CAR BOOK	Working Voltage: 9-60V DC	22 inch	120W	6pcs	Get Price
3 Kinds of		Housing: Die-cast Aluminum	28 inch	150W	6pcs	Get Price
Mount		Mounting: Stainless Steel	34 inch	180W	4pcs	Get Price
Methods	600 L	IP Rating: IP68	40 inch	210W	4pcs	Get Price
		Life-span: 50,000 Hours Product Warranty: 1 Year	46 inch	240W	4pcs	Get Price
NEW		110duct warranty. 1 Tear	52 inch	270W	4pcs	Get Price
			32 men	27011	ipes	GetTitee
JT-3500	LED Chip: 10W Cl Effective Lumen: 86l Working Voltage: 9-6 Housing: Die-cast Alu Mounting: Stainless	Beam Optional: Spot/Flood/Combo  LED Chip: 10W CREE	16 inch	90W	брсѕ	Get Price
Curved, 3 Mount Methods		Working Voltage: 9-60V DC Housing: Die-cast Aluminum Mounting: Stainless Steel	22 inch	120W	брсѕ	Get Price
NEW	2.4.2.4.2.5.2.2.2.2.2.2.2.2.2.2.2.2.2.2.	IP Rating: IP68 Life-span: 50,000 Hours Product Warranty: 1 Year	46 inch	270W	4pcs	Get Price
			6 inch	30W	12pcs	Get Price
JT-2300		Beam Optional: Spot/Flood/Combo	11.3 inch	60W	12pcs	Get Price
		LED Chip: 10W CREE Effective Lumen: 70LM/W	16.6 inch	90W	6pcs	Get Price
10W		Working Voltage: 9-60V DC	21.9 inch	120W	6pcs	Get Price
CREE	- <b>666</b> 666 -	Housing: Die-cast Aluminum	27.2 inch	150W	6pcs	Get Price
	<del>2</del>	Mounting: Stainless Steel	32.6 inch	180W	4pcs	Get Price
Straight	900 000 000 ecc	IP Rating: IP68	37.9 inch	210W	4pcs	Get Price
<b>XX</b> /L:4 - 0		Life-span: 50,000 Hours	43.2 inch	240W	4pcs	Get Price
White & Amber		Product Warranty: 1 Year	48.5 inch 53.8 inch	270W 300W	4pcs	Get Price Get Price
Ambel			4.3 inch	20W	4pcs 20pcs	Get Price
JT-2500		Beam Optional: Spot/Flood/Combo	7.3 inch	40W	12pcs	Get Price
0 2 2000		LED Chip: 10W CREE	10.4 inch	60W	12pcs	Get Price
		Effective Lumen: 70LM/W	13.5 inch	80W	12pcs	Get Price
10W	COLE SECTION	Working Voltage: 9-40V DC	19.6 inch	120W	6pcs	Get Price
CREE	0.000	Housing: Die-cast Aluminum Mounting: Stainless Steel	23 inch	140W	6pcs	Get Price
Ctroight		IP Rating: IP68	32 inch	200W	6pcs	Get Price
Straight		Life-span: 50,000 Hours	41 inch	260W	4pcs	Get Price
		Product Warranty: 1 Year	47 inch	300W	4pcs	Get Price
			51 inch	320W	4pcs	Get Price

			4.6 inch	20W	20pcs	Get Price
JT-1100		Beam Optional: Spot/Flood	7.8 inch	40W	10pcs	Get Price
	•	LED Chip: 10W CREE	10.9 inch	60W	10pcs	Get Price
10W		Effective Lumen: 86LM/W Working Voltage: 9-60V DC	17.2 inch	100W	6pcs	Get Price
CREE		Housing: Die-cast Aluminum	20.3 inch	120W	6pcs	Get Price
		Mounting: Stainless Steel	29.7 inch	180W	4pcs	Get Price
Straight		IP Rating: IP68 Life-span: 50,000 Hours	39.1 inch	240W	4pcs	Get Price
4D Lens	elefelelefelefelefelefelej	Product Warranty: 1 Year	42.2 inch	260W	4pcs	Get Price
4D Lens			50 inch	300W	2pcs	Get Price
JT-3100		Beam Optional: Spot/Flood/Combo	7.5 inch	36W	брсѕ	Get Price
31-3100	~~	LED Chip: 3W CREE	13.5 inch	72W	6pcs	Get Price
CDEE	1 Ja	Effective Lumen: 80LM/W Working Voltage: 10-30V DC	21.5 inch	120W	6pcs	Get Price
CREE Straight		Housing: Die-cast Aluminum	31.5 inch	180W	4pcs	Get Price
		Mounting: Alu Firm Bracket IP Rating: IP68	41.5 inch	240W	4pcs	Get Price
4D Lens	distanting states (S.	Life-span: 50,000 Hours Product Warranty: 1 Year	50 inch	288W	4pcs	Get Price
TO Letts			54 inch	300W	4pcs	Get Price
JT-2800	22222	Beam Optional: Spot/Flood/Combo  LED Chip: 3W CREE  Effective Lumen: 70LM/W  Working Voltage: 10, 30V DC	13.5 inch	72W	брсѕ	Get Price
31-2000			21.5 inch	120W	брсѕ	Get Price
CREE	3D Optical Lens Bar Normal Reflector Bar	Working Voltage: 10-30V DC Housing: Die-cast Aluminum Mounting: Alu Firm Bracket	31.5 inch	180W	4pcs	Get Price
Curved		IP Rating: IP68 Life-span: 50,000 Hours	41.5 inch	240W	4pcs	Get Price
3D Lens		Product Warranty: 1 Year	50 inch	288W	4pcs	Get Price
		Decree One in the State //Elecat/Country	7.5 inch	36W	6pcs	Get Price
JT-2900	*********	Beam Optional: Spot/Flood/Combo LED Chip: 3W CREE	13.5 inch	72W	6pcs	Get Price
		Effective Lumen: 70LM/W Working Voltage: 10-30V DC	21.5 inch	120W	6pcs	Get Price
CREE	3D Optical Lens Bar Normal Reflector Bar	Housing: Die-cast Aluminum	31.5 inch	180W	4pcs	Get Price
Straight		Mounting: Alu Firm Bracket IP Rating: IP68	41.5 inch	240W	4pcs	Get Price
3D Lens		Life-span: 50,000 Hours Product Warranty: 1 Year	50 inch	288W	4pcs	Get Price
JD Lells	19 m	2100000 (Autum) 1 1001	54 inch	300W	4pcs	Get Price
			5 inch	15W	20pcs	Get Price
JT-S05-B		Beam Optional: Spot/Flood/Combo	9 inch	30W	16pcs	Get Price
		LED Chip: 5W CREE Effective Lumen: 70LM/W	12.8 inch	45W	10pcs	Get Price
5W	O COASO	Working Voltage: 9-32V DC	16.8 inch	60W	8pcs	Get Price
CREE		Housing: Die-cast Aluminum	20.8 inch 25 inch	75W 90W	6pcs	Get Price Get Price
	6000000	Mounting: Alu Firm Bracket	28.7 inch	105W	6pcs	Get Price
Straight		IP Rating: IP68 Life-span: 50,000 Hours	33 inch	120W	6pcs	Get Price
		Product Warranty: 1 Year	40.5 inch	150W	4pcs	Get Price
			49 inch	180W	4pcs	Get Price

JT-S05-C		Beam Optional: Spot/Flood/Combo LED Chip: 5W CREE	10.8 inch	30W	6pcs	Get Price
5W CREE		Effective Lumen: 86LM/W Working Voltage: 9-60V DC Housing: Die-cast Aluminum	20.3 inch	60W	брсѕ	Get Price
Straight	2	Mounting: Alu Firm Bracket IP Rating: IP68 Life-span: 50,000 Hours	29.7 inch	90W	4pcs	Get Price
		Product Warranty: 1 Year	39.2 inch	120W	4pcs	Get Price
			6.8 inch	30W	6pcs	Get Price
JT-S05-D	SERVICE OF THE PERSON NAMED IN COLUMN TWO IS NOT THE PERSON NAMED IN COLUMN TWO IS	Beam Optional: Spot/Flood/Combo LED Chip: 5W CREE	13 inch	60W	6pcs	Get Price
		Effective Lumen: 70LM/W Working Voltage: 9-32V DC Housing: Die-cast Aluminum Mounting: Alu Firm Bracket IP Rating: IP68 Life-span: 50,000 Hours Product Warranty: 1 Year	19.1 inch	90W	6pcs	Get Price
5W	The state of the s		25.2 inch	120W	6pcs	Get Price
CREE			31.4 inch	150W	4pcs	Get Price
Straight			37.5 inch	180W	4pcs	Get Price
Amber/			43.7 inch	210W	4pcs	Get Price
White			49.8 inch	240W	4pcs	Get Price
	-		3.9 inch	36W	12pcs	Get Price
JT-2200		Beam Optional: Spot/Flood/Combo LED Chip: 3W CREE	6.6 inch	72W	6pcs	Get Price
	The second secon	Effective Lumen: 68LM/W	9.3 inch	108W	8pcs	Get Price
CREE		Working Voltage: 9-32V DC Housing: Die-cast Aluminum	12 inch	144W	6pcs	Get Price
		Mounting: Stainless Steel	14.6 inch	180W	6pcs	Get Price
Straight	Committee (IIII)	IP Rating: IP65 Life-span: 50,000 Hours	17.3 inch	216W	6pcs	Get Price
4 Row	-	Product Warranty: 1 Year	20 inch	252W	6pcs	Get Price
4 NUW		·	22.7 inch	288W	6pcs	Get Price

- 1. MOQ: One CTN(Carton)/Model, Price Term: EXW Factory without Delivery or FOB Charges;
- 2. Payment Method: TT/Paypal/Western Union/Escrow (Transfer charge paid by buyer side);
- 3. Packing: Plain white box without logo, Custom Logo can be engraved per your request;
- 4. Delivery: 1-7 days for samples; 7-30 days for bulk production;
- 5. One year warranty and life-long after-sale services provided;
- 6. Quote valid date: 30 days since this quotation received.



## juntu See Guangzhou Juntu Auto Accessories Co., Ltd.

Contact: Mike Zheng Email: sales7@juntu-auto.com Mob/Whatsapp: +8615899973510

Skype: Sales7-mike Facebook/Wechat: mike652638 Website: www.juntu-auto.com

### **Product List for LED Driving/Work Lights**

Model	Picture for Reference Contact Mike for More Pictures	Spe	ecification	Pacl	king Details	Get Price Via Email Inquiry
JT-1540	To a	Beam Optional LED Chip	Spot/Flood 10W CREE	PCs/ctn	12pcs	
		Power Lumen	40W 3500 LM	N.W/pc	1.25kg	
4 inch	A MONTH	Working Voltage Current Draw	9-32V DC 2.7A@12V,1.3A@24V	G.W/ctn	16.0kg	Get Price
40W		Housing Materials Mouting Bracket	Die-cast Aluminum Stainless Steel	CTN Size	48*38*30cm	
нот		IP Rating Life-span	IP68 50,000 Hours	CTN Vol.	0.055m³	
	A F	Beam Optional LED Chip	Spot/Flood/Combo/Euro 10W CREE	PCs/ctn	8pcs	
JT-1570		Power Lumen	70W 5000 LM	N.W/pc	1.95kg	
6 inch		Working Voltage Current Draw		G.W/ctn	16.0kg	<b>Get Price</b>
70W			Die-cast Aluminum	CTN Size	49*39*31cm	
нот		IP Rating Life-span	IP68 50,000 Hours	CTN Vol.	0.059m³	
		Beam Optional LED Chip	Spot Beam 25W CREE COB	PCs/ctn	12pcs	
JT-3400		Power Lumen	25W 25W 1800 LM	N.W/pc	1.10kg	
4.7 inch		Working Voltage Current Draw		G.W/ctn	17.0kg	Get Price
25W			Die-cast Aluminum	CTN Size	48*38*30cm	
нот		IP Rating Life-span	IP68 50,000 Hours	CTN Vol.	$0.055 \text{m}^3$	
		Beam Optional LED Chip	Spot Beam 15W CREE COB	PCs/ctn	8pcs	
JT-3700		Power Lumen	45W 3200LM	N.W/pc	1.50kg	
7 inch 45W		Working Voltage Current Draw		G.W/ctn	13.5kg	Get Price
Black/Red /Chrome			Die-cast Aluminum	CTN Size	53*44*40cm	
HOT		IP Rating Life-span	IP68 50,000 Hours	CTN Vol.	0.093m³	

				ı		
	1	Beam Optional LED Chip	Spot Beam 10W CREE	PCs/ctn	6pcs	
JT-1670		Power	70W			
	0 3 3	Lumen	6000 LM	N.W/pc	2.50kg	
		Working Voltage				
7 inch		Current Draw	4.5A@12V,2.3A@24V	G.W/ctn	15.0kg	<b>Get Price</b>
70W	1625		Die-cast Aluminum			
	1000	Mouting Bracket		CTN Size	48*27*39cm	
		IP Rating	IP68			
NEW		Life-span	50,000 Hours	CTN Vol.	$0.051 \text{m}^3$	
		Beam Optional	Spot Beam	PCs/ctn	<b>En</b> as	
JT-1690	1	LED Chip	10W CREE	PCS/Ctil	6pcs	
J1-1090		Power	90W	N.W/pc	2.50kg	
		Lumen	7200 LM	14. W/pc	2.30Kg	
	000 N 2 2 2 2 2 3 1	Working Voltage	9-32V DC	G.W/ctn	15 0kg	<b>Get Price</b>
7 inch	THE REPORT OF	Current Draw	6.2A@12V,3.0A@24V	G. W/eth	13.0Kg	Gerriee
90W	A . 5 36 7	_	Die-cast Aluminum	CTN Size	48*27*39cm	
	1000	Mouting Bracket				
NEW		IP Rating	IP68	CTN Vol.	$0.051 \text{m}^3$	
		Life-span	50,000 Hours			
	·	Beam Optional LED Chip	Spot Beam 10W CREE	PCs/ctn	4pcs	
JT-16120	6363	Power	120W			
		Lumen	10000LM	N.W/pc	3.60kg	
	3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	Working Voltage				
9 inch	* R. R. R. R.	Current Draw	7.9A@12V,4.3A@24V	G.W/ctn	16.5kg	<b>Get Price</b>
120W			Die-cast Aluminum			
	6. 60	Mouting Bracket		CTN Size	56*34*38cm	
NIEWY	·	IP Rating	IP68	CTNI V. 1	0.0723	
NEW		Life-span	50,000 Hours	CTN Vol.	0.072m <sup>3</sup>	
		Beam Optional	Spot/Flood Cover	PCs/ctn	4pcs	
JT-15225	juntuseia	LED Chip	5W CREE	1 CS/CtII	трез	
01 10220		Power	225W	N.W/pc	4.00kg	
		Lumen	19350 LM			
		Working Voltage		G.W/ctn	17.0kg	<b>Get Price</b>
9 inch 225W		Current Draw	15.8A@12V,8A@24V		-	
223 W		Mouting Bracket	Die-cast Aluminum	CTN Size	52*34*32cm	
		IP Rating	IP68			
NEW	NEW 9INCH 225W CREE	Life-span	50,000 Hours	CTN Vol.	$0.057 \text{m}^3$	
		Beam Optional	High/Low Beam			
7''*5''		LED Chip	5W CREE	PCs/ctn	12pcs	
Square		Power	60W(High)/30W(Low)	NY 1777	1.201	
		Lumen	5200 LM/ 2600LM	N.W/pc	1.20kg	
12*5W		Working Voltage	9-32V DC	G.W/ctn	15 Oka	Cat Dries
Truck		Current Draw	4.1A@12V,2.0A@24V	J. W/CIII	13.UKg	Get Price
Head		· ·	Die-cast Aluminum	CTN Size	50*35*35cm	
Light		Mouting Bracket			20 23 33cm	
нот		IP Rating	IP68	CTN Vol.	$0.061 \text{m}^3$	
		Life-span	50,000 Hours			

		Beam Optional	High/Low Beam			
4"x6"		LED Chip	3W Epistar	PCs/ctn	20pcs	
Square		Power	45W(High)/15W(Low)			
Square	Can an an an and	Lumen	3500 LM/ 1200LM	N.W/pc	0.90kg	
45W		Working Voltage				
Truck	1 5 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6	Current Draw	2.1A@12V,1.5A@24V	G.W/ctn	18.5kg	<b>Get Price</b>
Head	0 0 0		Die-cast Aluminum			
Light	The same of the sa	Mouting Bracket		CTN Size	50*37*32cm	
High/low		IP Rating	IP68			
Beam		Life-span	50,000 Hours	CTN Vol.	$0.059 \text{m}^3$	
Deam		Beam Optional	High/low Beam			
	0	LED Chip	3W Epistar	PCs/ctn	24pcs	
JT-2845	3) 3) 3) 4) 4) 6) 11 1	Power	45W			
	AL PUR NO.	Lumen	3150 LM	N.W/pc	1.15kg	
	A LOCAL CONTRACTOR OF THE PARTY	Working Voltage				
6.5 inch		Current Draw	3.4A@12V,1.6A@24V	G.W/ctn	27.0kg	<b>Get Price</b>
45W			Die-cast Aluminum			
HeadLight	(3)	Mouting Bracket		CTN Size	54*39*27cm	
High/low		IP Rating	IP68			
Beam		Life-span	50,000 Hours	CTN Vol.	$0.057 \text{m}^3$	
Deam		Beam Optional	High/Low Beam			
	0.004-0	LED Chip	3W/15W Epistar	PCs/ctn	24pcs	
JT-2942		Power	42W			
		Lumen	3000LM	N.W/pc	0.70kg	
		Working Voltage				
6.5inch		Current Draw	1.9A@12V,1.4A@24V	G.W/ctn	17.8kg	<b>Get Price</b>
45W	26600		Die-cast Aluminum			
HeadLight		Mouting Bracket		CTN Size	59*38*31cm	
High/low	5	IP Rating	IP68			
Beam		Life-span	50,000 Hours	CTN Vol.	$0.070 \text{m}^3$	
		Beam Optional	Combo Beam			
	9	LED Chip	3W Epistar	PCs/ctn	16pcs	
JT-2730	6	Power	30W	NY 1777	4 0.01	
		Lumen	1820 LM	N.W/pc	1.00kg	
		Working Voltage	9-40V DC	G ****	4 7	G . D .
5.5 inch	3	Current Draw	1.4A@12V,1.2A@24V	G.W/ctn	15.6kg	Get Price
30W		Housing Materials	Die-cast Aluminum	CENT C.	CC+20+24	
	19	Mouting Bracket	Stainless Steel	CTN Size	66*30*24cm	
High/low	8	IP Rating	IP68	CTNI V. 1	0.0403	
Beam		Life-span	50,000 Hours	CTN Vol.	0.048m <sup>3</sup>	
		Beam Optional	Combo Beam	DCs/atm	24nos	
JT-2745		LED Chip	3W Epistar	PCs/ctn	24pcs	
J1-2/45		Power	45W	N.W/pc	1.15kg	
		Lumen	3500LM	11. W/pc	1.13Ng	
5.5 inch	166	Working Voltage	9-32V DC	G.W/ctn	27 Oka	Get Price
3.3 mcn 36W		Current Draw	2.7A@12V,1.3A@24V	J. 17/CIII	21.UNG	GetTite
HeadLight		· ·	Die-cast Aluminum	CTN Size	54*39*27cm	
Trauligill		Mouting Bracket	Stainless Steel	CIN SIZE	57 57 2/CIII	
High/low		IP Rating	IP68	CTN Vol.	0.057m <sup>3</sup>	
Beam		Life-span	50,000 Hours	C114 VOI.	0.05/111	

5 inch Round 36W		Beam Optional LED Chip Power	Spot Beam 3W Epistar 36W	PCs/ctn N.W/pc	20pcs 0.60kg	
Truck Head		Lumen Working Voltage Current Draw	2.2A@12V,1.1A@24V	G.W/ctn	· ·	Get Price
Light		Housing Materials Mouting Bracket	Die-cast Aluminum Stainless Steel	CTN Size	51*32*32cm	
		IP Rating Life-span	IP68 50,000 Hours	CTN Vol.	$0.052m^3$	
JT-1936		Beam Optional LED Chip	Combo Beam 3W Epistar	PCs/ctn	20pcs	
31-1930	a Roa	Power Lumen	36W 2520 LM	N.W/pc	1.00kg	
5.5 inch 36W		Working Voltage Current Draw	9-32V DC 1.8A@12V,0.9A@24V	G.W/ctn	21.0kg	<b>Get Price</b>
HeadLight	00	Housing Materials Mouting Bracket	Die-cast Aluminum Stainless Steel	CTN Size	49*31*33cm	
High/low Beam		IP Rating Life-span	IP68 50,000 Hours	CTN Vol.	0.050m³	
4 inch Square		Beam Optional LED Chip	Spot Beam 3W Epistar	PCs/ctn	20pcs	
24W		Power Lumen	24W 1900 LM	N.W/pc	0.70kg	
Truck Head		Working Voltage Current Draw	1.6A@12V,0.7A@24V	G.W/ctn	14.5kg	<b>Get Price</b>
Light		Housing Materials  Mouting Bracket	Die-cast Aluminum Stainless Steel	CTN Size	48*34*25cm	
	U	IP Rating Life-span	IP68 50,000 Hours	CTN Vol.	0.041m³	
4 inch Round		Beam Optional LED Chip	Spot Beam 3W Epistar	PCs/ctn	20pcs	
21W		Power Lumen	21W 1700 LM	N.W/pc	0.50kg	
Truck Head		Working Voltage Current Draw	1.4A@12V,0.7A@24V	G.W/ctn	10.7kg	Get Price
Light	9	Mouting Bracket		CTN Size	48*34*25cm	
		IP Rating Life-span	IP68 50,000 Hours	CTN Vol.	0.041m³	
JT-1818		Beam Optional LED Chip	Spot Beam 3W CREE	PCs/ctn	20pcs	
<b>61 1010</b>		Power Lumen	18W 1180LM	N.W/pc	0.80kg	
4 inch 18W		Working Voltage Current Draw	9-32V DC 1.1A@12V,0.5A@24V	G.W/ctn	17.0kg	<b>Get Price</b>
Back-up Light		Housing Materials Mouting Bracket	Die-cast Aluminum Stainless Steel	CTN Size	50*30*24cm	
NEW		IP Rating Life-span	IP68 50,000 Hours	CTN Vol.	0.036m³	

	444444	Beam Optional	Spot/Flood	PCs/ctn	20pcs	
JT-2812	10000000	LED Chip	3W CREE		1	
		Power	12W	N.W/pc	0.35kg	
		Lumen	840LM	, p•	0.55115	
		Working Voltage	9-32V DC	G.W/ctn	7 3kg	<b>Get Price</b>
2.8 inch		Current Draw	0.8A@12V,0.4A@24V	G. W/Ctil	7.5Kg	GetTitee
12W	(III)	Housing Materials	Die-cast Aluminum	CTN Size	53*17*20cm	
	TI at	Mouting Bracket	Stainless Steel		33 17 20cm	
NEW		IP Rating	IP68	CTN Vol.	0.018m3	
141244	U	Life-span	50,000 Hours	CIN VOI.	0.010111	
		Beam Optional	Spot/Flood	PCs/ctn	20pcs	
JT-2815		LED Chip	3W CREE	1 05/0011	Zopes	
J1-2013		Power	15W	N.W/pc	0.65kg	
		Lumen	1050LM	14. W/pc	0.03kg	
		Working Voltage	9-32V DC	G.W/ctn	12.5kg	<b>Get Price</b>
3 inch		Current Draw	0.9A@12V,0.5A@24V	G. W/Ctil	13.3kg	GetTite
15W		Housing Materials	Die-cast Aluminum	CTN Size	37*34*28cm	
		Mouting Bracket	Stainless Steel	CIN Size	37.34.200111	
NEW		IP Rating	IP68	CTN Vol.	0.0253	
INIC VV		Life-span	50,000 Hours	CIN VOI.	0.0531119	
		Beam Optional	Spot/Flood	PCs/ctn	19nas	
JT-2912	0	LED Chip	3W CREE	PCS/CIII	18pcs	
J1-2912		Power	12W	N.W/pc	0.90kg	
	0	Lumen	1080LM	IN. W/pc	0.90kg	
3 inch		Working Voltage	10-30V DC	G.W/ctn	17 Oka	Cat Dries
12W		Current Draw	1.4A@12V,0.7A@24V	G. W/Ctil	17.0Kg	Get Price
LED Pod		Housing Materials	Die-cast Aluminum	CTN Circ	33*23*42cm	
LED I Ou	1	Mouting Bracket	Stainless Steel	CIN Size	55°25°42CIII	
нот	Y	IP Rating	IP68	CTN Vol.	0.022m3	
HOI	•	Life-span	50,000 Hours	CIN VOI.	0.032III <sup>3</sup>	
		Beam Optional	Spot/Flood	PCs/ctn	18pcs	
JT-2918	e o	LED Chip	3W CREE	1 Cs/Ctil	Topes	
J1-2710		Power	18W	N.W/pc	0.90kg	
		Lumen	1620LM	11. W/pc	0.70kg	
3 inch	SIGGO	Working Voltage	10-30V DC	G.W/ctn	14 Oka	Get Price
18W		Current Draw	1.4A@12V,0.7A@24V	J. W/CIII	17.UKg	GetTite
LED Pod	0	Housing Materials	Die-cast Aluminum	CTN Size	33*23*42cm	
		Mouting Bracket	Stainless Steel		55 25 <b>720</b> 111	
нот	T	IP Rating	IP68	CTN Vol.	0.032m³	
1101	•	Life-span	50,000 Hours	CIIV VOI.	0.032111	
		Beam Optional	Spot/Flood	PCs/ctn	18pcs	
JT-4912		LED Chip	3W CREE	25/011	Topes	
J1-4/12	(0,0)	Power	12W	N.W/pc	1.00kg	
		Lumen	1080LM	11. 11/pc	1.00Kg	
4.8 inch		Working Voltage	10-30V DC	G.W/ctn	19 Oka	<b>Get Price</b>
4.8 inch 12W		Current Draw	1.4A@12V,0.7A@24V	J. 77/CIII	17.UKg	GetTite
LED Pod		Housing Materials	Die-cast Aluminum	CTN Size	42*35*24cm	
100	0	Mouting Bracket	Stainless Steel	C 114 SIZE	72 33 24CIII	
нот		IP Rating	IP68	CTN Vol.	$0.035m^3$	
1101		Life-span	50,000 Hours	CIII VOI.	0.033111	

		1		1		·
		Beam Optional	Spot/Flood	PCs/ctn	20pcs	
JT-4818		LED Chip	3W CREE			
		Power	18W	N.W/pc	0.75kg	
		Lumen	1620LM		-	
4.8 inch		Working Voltage		G.W/ctn	15.2kg	<b>Get Price</b>
18W		Current Draw	1.5A@12V,0.7A@24V		C	
LED Pod			Die-cast Aluminum	CTN Size	33*28*62cm	
		Mouting Bracket				
нот		IP Rating	IP68	CTN Vol.	$0.057 \text{m}^3$	
		Life-span	50,000 Hours	011, , 01.		
		Beam Optional	Spot/Flood	PCs/ctn	20pcs	
JT-2718		LED Chip	3W Epistar	1 Co/Ctil	2000	
31-2/10	aga	Power	18W	N.W/pc	0.90kg	
	933	Lumen	1080 LM	14. W/pc	0.70kg	
		Working Voltage	9-32V DC	G.W/ctn	10 Oka	<b>Get Price</b>
3 inch		Current Draw	1.0A@12V,0.5A@24V	G. W/CIII	19.0kg	Get Frice
18W	ilalia no.	Housing Materials	Die-cast Aluminum	CTN Size	33*23*42cm	
		Mouting Bracket	Stainless Steel	CTN Size	55*25*42CIII	
NIEUWY		IP Rating	IP68	CTNI V. 1	0.022 3	
NEW		Life-span	50,000 Hours	CTN Vol.	0.032m <sup>3</sup>	
		Beam Optional	Spot/Flood	DC / /	20	
IT 2525	0000	LED Chip	3W CREE	PCs/ctn	20pcs	
JT-2527	<b>公司</b>	Power	27W	N 1 1 1 1 1 /	0.001	
		Lumen	1890 LM	N.W/pc	0.90kg	
	222	Working Voltage	9-32V DC	G ****	40.01	~ . ~ .
4 inch	でデージを計画し	Current Draw	1.5A@12V,0.8A@24V	G.W/ctn	19.0kg	<b>Get Price</b>
27W		Housing Materials	Die-cast Aluminum	amy at		
		Mouting Bracket		CTN Size	33*23*42cm	
		IP Rating	IP68			
NEW	T T	Life-span	50,000 Hours	CTN Vol.	$0.032 \text{m}^3$	
		Beam Optional	Spot/Flood	D.G. /		
	( DE )	LED Chip	5W CREE	PCs/ctn	20pcs	
JT-2530		Power	30W			
		Lumen	2100 LM	N.W/pc	0.90kg	
		Working Voltage				
4 inch		Current Draw	1.9A@12V,1.0A@24V	G.W/ctn	19.0kg	Get Price
30W			Die-cast Aluminum	amaz si		
		Mouting Bracket		CTN Size	33*23*42cm	
		IP Rating	IP68			
NEW	T	Life-span	50,000 Hours	CTN Vol.	$0.032m^3$	
		Beam Optional	Spot/Flood			
		LED Chip	10W CREE	PCs/ctn	20pcs	
JT-2740		Power	40W			
	100	Lumen	2800 LM	N.W/pc	0.75kg	
		Working Voltage				
4 inch		Current Draw	2.9A@12V,1.4A@24V	G.W/ctn	15.2kg	<b>Get Price</b>
40W			Die-cast Aluminum			
	Mak.	Mouting Bracket		CTN Size	33*28*62cm	
	0000	IP Rating	IP68			
NEW		Life-span	50,000 Hours	CTN Vol.	$0.057 \text{m}^3$	
		Enc-span	50,000 Hours			

		Beam Optional	Spot/Flood			
VIII. 40.40		LED Chip	3W Epistar	PCs/ctn	20pcs	
JT-2848		Power	48W		0.004	
		Lumen	3840 LM	N.W/pc	0.90kg	
		Working Voltage	9-32V DC	C W/	01.01	G (P)
4 inch		Current Draw	3.8A@12V,1.9A@24V	G.W/ctn	21.0kg	Get Price
48W		Housing Materials	Die-cast Aluminum	CENT C.	0.4 * 0.1 * 40	
		Mouting Bracket	Stainless Steel	CIN Size	34*31*49cm	
NEW		IP Rating	IP68	CTN Val	0.0523	
INE VV	- U	Life-span	50,000 Hours	CTN Vol.	0.0321115	
		Beam Optional	Spot/Flood	PCs/ctn	20pcs	
JT-2750		LED Chip	10W CREE	1 Cs/Ctil	Zopes	
J1-2/30	The second second	Power	50W	N.W/pc	0.90kg	
	A SUM	Lumen	3500 LM	14. W/pc	0.70Kg	
		Working Voltage	9-32V DC	G.W/ctn	19 Oko	<b>Get Price</b>
5 inch		Current Draw	3.4A@12V,1.6A@24V	S. Wyeth	17.016	Gerrice
50W			Die-cast Aluminum	CTN Size	33*23*42cm	
		Mouting Bracket				
NEW		IP Rating	IP68	CTN Vol.	0.032m <sup>3</sup>	
_ ,_ ,,	40	Life-span	50,000 Hours			
		Beam Optional	Spot/Flood	PCs/ctn	20pcs	
JT-2860	CHANGE !	LED Chip	5W CREE		•	
		Power	60W	N.W/pc	1.00kg	
		Lumen	4200LM		<u> </u>	
Z : 1		Working Voltage		G.W/ctn	22.0kg	<b>Get Price</b>
5 inch	2252333	Current Draw	3.9A@12V,2.0A@24V			
60W	71 1585		Die-cast Aluminum	CTN Size	34*31*49cm	
		Mouting Bracket				
NEW		IP Rating Life-span	IP68 50,000 Hours	CTN Vol.	$0.052m^3$	
	-	Beam Optional	Flood			
JT-1210-		LED Chip	3W Epistar	PCs/ctn	20pcs	
15W		Power	15W			
		Lumen	850LM	N.W/pc	0.65kg	
	10 49	Working Voltage				
		Current Draw	1.1A@12V,0.6A@24V	G.W/ctn	14.0kg	<b>Get Price</b>
4.3 inch			Die-cast Aluminum	OTEN C:	20420422	
		Mouting Bracket		CIN Size	30*29*32cm	
		IP Rating	IP68	CTN V-1	0.0203	
		Life-span	50,000 Hours	CTN Vol.	0.028M³	
		Beam Optional	Spot/Flood	PCs/ctn	20pcs	
JT-1210-	6 6	LED Chip	3W Epistar	1 CS/CIII	20pcs	
15W-A	3 3	Power	15W	N.W/pc	0.65kg	
	4	Lumen	850LM	1, pc	0.03Rg	
	ER	Working Voltage		G.W/ctn	13.5kg	Get Price
4.3 inch		Current Draw	1.0A@12V,0.4A@24V		-2.2.2	SUPPLE
			Die-cast Aluminum	CTN Size	37*34*28cm	
	THE PARTY OF	Mouting Bracket			2. 2. 20011	
		IP Rating	IP68	CTN Vol.	$0.035 \text{m}^3$	
		Life-span	50,000 Hours			

		Beam Optional	Flood			
JT-1205-		LED Chip	3W Epistar	PCs/ctn	20pcs	
18W		Power	18W			
1011		Lumen	1000LM	N.W/pc	0.60kg	
		Working Voltage				
		Current Draw	1.3A@12V,0.6A@24V	G.W/ctn	12.5kg	<b>Get Price</b>
4.5 inch	The same of the sa		Die-cast Aluminum			
		Mouting Bracket		CTN Size	30*29*32cm	
		IP Rating	IP68			
BULK	7300	Life-span	50,000 Hours	CTN Vol.	$0.028 \text{m}^3$	
	-	Beam Optional	Spot/Flood	DG /	20	
JT-1205-		LED Chip	3W Epistar(/CREE)	PCs/ctn	20pcs	
18W-A		Power	18W	NI XX//	0.651	
		Lumen	1000LM	N.W/pc	0.65kg	
	HAAI	Working Voltage	9-32V DC	C W/sta	10.51	C A D
1 5 in ala		Current Draw	1.1A@12V,0.5A@24V	G.W/ctn	13.5Kg	<b>Get Price</b>
4.5 inch		Housing Materials	Die-cast Aluminum	CTN Circ	37*34*28cm	
	A	Mouting Bracket	Stainless Steel	CIN Size	37*34*28CIII	
BULK		IP Rating	IP68	CTN Vol.	0.025m3	
BULK	U	Life-span	50,000 Hours	CIN VOI.	0.033111	
		Beam Optional	Spot/Flood	PCs/ctn	20pcs	
JT-1210-	and the same	LED Chip	3W Epistar	1 CS/CtII	Zopes	
24W	・一般性の思う無限	Power	24W	N.W/pc	0.70kg	
	一带,一个人	Lumen	1250LM	11. W/pc	0.70Kg	
		Working Voltage	9-32V DC	G.W/ctn	14 5kg	<b>Get Price</b>
4.3 inch		Current Draw	1.8A@12V,0.9A@24V	G. Wyeth	11.3Kg	Gerrice
		, and the second	Die-cast Aluminum	CTN Size	37*34*28cm	
		Mouting Bracket				
BULK	1	IP Rating	IP68	CTN Vol.	0.035m <sup>3</sup>	
		Life-span	50,000 Hours			
YE 1205	22	Beam Optional	Spot/Flood	PCs/ctn	20pcs	
JT-1205- 24W	3 ATTION	LED Chip	3W Epistar		_	
24 VV		Power	24W	N.W/pc	0.70kg	
		Lumen	1250LM			
	3	Working Voltage Current Draw	9-32V DC 1.8A@12V,0.9A@24V	G.W/ctn	14.5kg	<b>Get Price</b>
4.3 inch	3		Die-cast Aluminum			
		Mouting Bracket		CTN Size	37*34*28cm	
		IP Rating	IP68			
BULK	The state of the s	Life-span	50,000 Hours	CTN Vol.	$0.035 \text{m}^3$	
		Beam Optional	Spot/Flood			
VIII 4 50=	The same of the sa	LED Chip	3W Epileds	PCs/ctn	20pcs	
JT-1627		Power	27W			
		Lumen	1050LM	N.W/pc	0.70kg	
	の金金の	Working Voltage	9-32V DC	CW/	14.51	C ( D )
4.5 inch		Current Draw	1.4A@12V,0.5A@24V	G.W/ctn	14.5Kg	<b>Get Price</b>
27W	The books	Housing Materials	Die-cast Aluminum	CTM C:	27*24*29	
		Mouting Bracket	Stainless Steel	CIN Size	37*34*28cm	
BULK	3	IP Rating	IP68	CTN Vol.	0.035m3	
DULK	U	Life-span	50,000 Hours	CIN VOI.	0.033IIF	

		Beam Optional	Spot/Flood	/		
		LED Chip	3W Epileds	PCs/ctn	20pcs	
JT-2627		Power	27W	NY 1777	0.701	
		Lumen	1050LM	N.W/pc	0.70kg	
	はの意識と	Working Voltage	9-32V DC	C W/otn	1.4.51	Cat Duine
4.2 inch		Current Draw	1.4A@12V,0.5A@24V	G.W/ctn	14.5Kg	<b>Get Price</b>
27W		Housing Materials	Die-cast Aluminum	CTN Size	37*34*28cm	
		Mouting Bracket	Stainless Steel	CTN SIZE	37 34 20cm	
BULK		IP Rating	IP68	CTN Vol.	0.035m <sup>3</sup>	
BCLIK		Life-span	50,000 Hours	CIIV VOI.	0.033111	
	(dimmonia)	Beam Optional	Spot/Flood	PCs/ctn	20pcs	
JT-1210-		LED Chip	3W Epistar		1	
27W		Power	27W	N.W/pc	0.80kg	
		Lumen	1400LM		_	
		Working Voltage		G.W/ctn	16.5kg	<b>Get Price</b>
4.3 inch		Current Draw	1.6A@12V,0.9A@24V Die-cast Aluminum			
		Mouting Bracket		CTN Size	37*34*28cm	
	F21	IP Rating	IP68			
	300	Life-span	50,000 Hours	CTN Vol.	$0.035 \text{m}^3$	
		Beam Optional	Spot/Flood			
JT-1205-		LED Chip	3W Epistar	PCs/ctn	20pcs	
27W		Power	27W	NI XX//	0.001-	
		Lumen	1400LM	N.W/pc	0.80kg	
		Working Voltage	9-32V DC	G.W/ctn	16.5kg	<b>Get Price</b>
4.3 inch	The state of the s	Current Draw	1.6A@12V,0.9A@24V	G. W/CIII	10.3kg	GetTite
1.5 men	Can De Car	Housing Materials	Die-cast Aluminum	CTN Size	37*34*28cm	
	The state of the s	Mouting Bracket			C, C. 200111	
		IP Rating	IP68	CTN Vol.	$0.035 \text{m}^3$	
		Life-span	50,000 Hours			
IT 1210		Beam Optional LED Chip	Spot/Flood	PCs/ctn	20pcs	
JT-1210- 18W		Power	3W Epistar 18W			
10 **	11111	Lumen	1580LM	N.W/pc	0.60kg	
		Working Voltage				
		Current Draw	1.4A@12V,0.8A@24V	G.W/ctn	12.3kg	<b>Get Price</b>
4.3 inch			Die-cast Aluminum	CENT C.	201/221/140	
	C. C.	Mouting Bracket	Stainless Steel	CTN Size	28*23*40cm	
		IP Rating	IP68	CTN Vol.	0.026-3	
		Life-span	50,000 Hours	CIIN VOI.	U.U∠UIII⁻	
		Beam Optional	Flood Beam	PCs/ctn	20pcs	
JT-1210-		LED Chip	3W Epistar	25,000	-op-0	
24W-2	Topod'	Power	24W	N.W/pc	0.80kg	
		Lumen	1200LM	_ ^	S	
		Working Voltage		G.W/ctn	16.5kg	<b>Get Price</b>
5.5 inch	31	Current Draw	1.6A@12V,0.8A@24V			
		Mouting Bracket	Die-cast Aluminum Stainless Steel	CTN Size	37*32*26cm	
		IP Rating	IP68			
		Life-span	50,000 Hours	CTN Vol.	$0.031 \text{m}^3$	
		Pum	,000 110010	<u> </u>		

		Beam Optional	Flood Beam			
JT-1210-		LED Chip	3W Epistar	PCs/ctn	12pcs	
33W		Power	33W			
3377	<b>a</b> a a a	Lumen	1650LM	N.W/pc	1.50kg	
		Working Voltage				
		Current Draw	1.9A@12V,1.1A@24V	G.W/ctn	19.0kg	<b>Get Price</b>
6.2 inch			Die-cast Aluminum			
		Mouting Bracket		CTN Size	41*37*32cm	
		IP Rating	IP68			
		Life-span	50,000 Hours	CTN Vol.	$0.049 \text{m}^3$	
		Beam Optional	Flood Beam			
JT-1210-		LED Chip	3W Epistar□	PCs/ctn	12pcs	
45W		Power	45W	NY 337/	1 501	
	<b>建</b> 建建建模型	Lumen	2250LM	N.W/pc	1.50kg	
	<b>新</b> 東本美生	Working Voltage	9-32V DC	C W/	10.01	C + D !
60:1	<b>建</b> 建设建设。	Current Draw	2.5A@12V,1.5A@24V	G.W/ctn	19.0kg	Get Price
6.2 inch	The state of the s	Housing Materials	Die-cast Aluminum	CTN Circ	41*27*22	
		Mouting Bracket	Stainless Steel	CTN Size	41*37*32cm	
		IP Rating	IP68	CTN Vol.	0.040m3	
		Life-span	50,000 Hours	CIN VOI.	0.049111	
		Beam Optional	Flood Beam	PCs/ctn	20pcs	
JT-1210-	Mannana	LED Chip	3W Epistar □	1 CS/CtII	Zopes	
27W-1	CORP	Power	27W	N.W/pc	1.10kg	
		Lumen	1400LM	14. 447 pc	1.10Kg	
		Working Voltage		G.W/ctn	23 3kg	<b>Get Price</b>
4.7 inch		Current Draw	1.5A@12V,0.9A@24V	G. VI eth	23.3Kg	GetTitee
27W		, and the second	Die-cast Aluminum	CTN Size	34*30*47cm	
	200	Mouting Bracket				
		IP Rating	IP68	CTN Vol.	$0.048 \text{m}^3$	
		Life-span	50,000 Hours			
IT 1210	The same	Beam Optional	Spot/Flood	PCs/ctn	12pcs	
JT-1210- 40W-1		LED Chip	10W CREE			
40 ** -1	<b>全种</b>	Power	40W 2800LM	N.W/pc	1.60kg	
	<b>基</b> 計劃	Lumen Working Voltage				
		Current Draw	3.3A@12V,1.7A@24V	G.W/ctn	20.5kg	<b>Get Price</b>
4.9 inch	世上		Die-cast Aluminum			
		Mouting Bracket		CTN Size	59*33*26cm	
Tempere		IP Rating	IP68			
d		Life-span	50,000 Hours	CTN Vol.	$0.051 \text{m}^3$	
	1.3	Beam Optional	Spot/Flood	DG /	•	
JT-1210-	0	LED Chip	3W Epistar	PCs/ctn	20pcs	
48W	9000	Power	48W	NT XX7/	0.001-	
		Lumen	2500LM	N.W/pc	0.90kg	
		Working Voltage	9-32V DC	C W/ot-	21 01-~	Cot Det =
1 2 in ah		Current Draw	3.8A@12V,1.9A@24V	G.W/ctn	21.UKg	Get Price
4.3 inch		Housing Materials	Die-cast Aluminum	CTN Sizo	34*31*49cm	
		Mouting Bracket	Stainless Steel	CIN SIZE	54 · 51 · 470III	
		IP Rating	IP68	CTN Vol.	0.052m³	
		Life-span	50,000 Hours	CIIV VUI.	0.0 <i>52</i> 111	

		Beam Optional	Spot/Flood			
		LED Chip	5W CREE	PCs/ctn	20pcs	
JT-1305		Power	5W CREE			
	Para A	Lumen	498LM	N.W/pc	0.15kg	
1.7 inch		Working Voltage				
5W		Current Draw	0.3A@12V,0.2A@24V	G.W/ctn	3.5kg	<b>Get Price</b>
Motor			Die-cast Aluminum			
Light	<b>3</b>	Mouting Bracket		CTN Size	38*24*19cm	
		IP Rating	IP68			
HOT		Life-span	50,000 Hours	CTN Vol.	$0.017 \text{m}^3$	
		Beam Optional	Spot/Flood	DG /	20	
IT 1210C		LED Chip	10W CREE	PCs/ctn	20pcs	
JT-1310C		Power	10W	NI XX//	0.401	
		Lumen	750LM	N.W/pc	0.40kg	
		Working Voltage	9-32V DC	C W/otro	0.01	Cat Daile
2 inch		Current Draw	0.9A@12V,0.4A@24V	G.W/ctn	9.0kg	Get Price
10W		Housing Materials	Die-cast Aluminum	CTN Size	56*26*17cm	
		Mouting Bracket	Stainless Steel	CIN Size	30·20·1/cm	
Black/	T	IP Rating	IP68	CTN Vol.	0.025m³	
White		Life-span	50,000 Hours	CIIV VOI.	0.023111	
		Beam Optional	Spot/Flood	PCs/ctn	20pcs	
JT-1312		LED Chip	3W Epistar		r	
	E 20	Power	12W	N.W/pc	0.50kg	
		Lumen	840LM	1	C	
		Working Voltage		G.W/ctn	10.3kg	<b>Get Price</b>
2.6 inch			0.9A@12V,0.4A@24V		C	
12W			Die-cast Aluminum	CTN Size	49*28*20cm	
	00	Mouting Bracket				
	6000	IP Rating	IP68	CTN Vol.	$0.027 m^3$	
		Life-span Beam Optional	50,000 Hours Spot/Flood			
JT-1205-		LED Chip	3W Epistar	PCs/ctn	40pcs	
12W		Power	12W			
12,11		Lumen	840 LM	N.W/pc	0.25kg	
		Working Voltage				
		Current Draw	0.6A@12V,0.3A@24V	G.W/ctn	21.0kg	<b>Get Price</b>
3.3inch			Die-cast Aluminum	OTEN C:	C 4 N O C N O 4	
		Mouting Bracket	Stainless Steel	CTN Size	64*36*21cm	
		IP Rating	IP68	CTN Vol.	0.0493	
		Life-span	50,000 Hours	CIN VOI.	U.U40III"	
	A CHARLES OF THE PARTY OF THE P	Beam Optional	Spot/Flood	PCs/ctn	40pcs	
JT-1205-		LED Chip	3W Epistar	25/001	торез	
9W		Power	9W	N.W/pc	0.22kg	
		Lumen	710 LM			
	1 Car	Working Voltage		G.W/ctn	9.8kg	<b>Get Price</b>
3.3 inch	125	Current Draw	0.6A@12V,0.3A@24V			
			Die-cast Aluminum	CTN Size	47*28*22cm	
	Manual Commence of the Commenc	Mouting Bracket				
		IP Rating	IP68	CTN Vol.	$0.029 \text{m}^3$	
		Life-span	50,000 Hours			

				T		1
	and the latest and th	Beam Optional	Spot/Flood	PCs/ctn	20pcs	
JT-1230	The state of the s	LED Chip Power	3W Epistar 12W			
		Lumen	840 LM	N.W/pc	0.35kg	
		Working Voltage				
3.3 inch	<b>医</b> 分别病医200	Current Draw	0.8A@12V,0.4A@24V	G.W/ctn	8.1kg	<b>Get Price</b>
12W			Die-cast Aluminum			
		Mouting Bracket		CTN Size	50*30*24cm	
		IP Rating	IP68			
		Life-span	50,000 Hours	CTN Vol.	0.036m³	
		Beam Optional	Spot/Flood	PCs/ctn	20pcs	
JT-4910		LED Chip	5W CREE	r Cs/ctii	Zopes	
J1-4710	DIA	Power	10W	N.W/pc	0.56kg	
		Lumen	700LM	11. W/pc	0.50kg	
3.8 inch		Working Voltage		G.W/ctn	9.5kg	<b>Get Price</b>
10W	K	Current Draw	0.8A@12V,0.4A@24V		, <u>8</u>	30011100
Forklift		_	Die-cast Aluminum	CTN Size	66*30*23cm	
Warning		Mouting Bracket				
White		IP Rating	IP68	CTN Vol.	$0.046 \text{m}^3$	
/Blue		Life-span Beam Optional	50,000 Hours Spot/Flood			
		LED Chip	10W CREE	PCs/ctn	20pcs	
JT-4920	a la	Power	20W			
		Lumen	1400LM	N.W/pc	0.56kg	
3.8 inch		Working Voltage				
20W	Se Service	Current Draw	1.6A@12V,0.8A@24V	G.W/ctn	9.5kg	Get Price
Forklift		Housing Materials	Die-cast Aluminum	CENT C.	5 5 th 2 O th 2 O	
Warning	C. C. C.	Mouting Bracket	Stainless Steel	CIN Size	66*30*23cm	
White		IP Rating	IP68	CTN Vol.	0.046m3	
/Blue		Life-span	50,000 Hours	CIN VOI.	0.040III°	
		Beam Optional	Spot/Flood	PCs/ctn	20pcs	
JT-1315		LED Chip	15W CREE COB		<b>-</b> 0 <b>p-</b> 0	
		Power	15W	N.W/pc	0.50kg	
		Lumen	1450LM		<u> </u>	
2 :1	1997	Working Voltage		G.W/ctn	11.5kg	<b>Get Price</b>
3 inch 15W		Current Draw	0.3A@12V,0.5A@24V			
13 **		Mouting Bracket	Die-cast Aluminum	CTN Size	66*30*24cm	
		IP Rating	IP68			
		Life-span	50,000 Hours	CTN Vol.	$0.048m^3$	
		Beam Optional	Spot/Flood	DG i		
TIT. 4030		LED Chip	15W CREE	PCs/ctn	12pcs	
JT-2830	16)	Power	30W	NI 337/	1 201	
		Lumen	2850LM	N.W/pc	1.30kg	
		Working Voltage	9-32V DC	G.W/ctn	16.6kg	<b>Get Price</b>
5.5 inch		Current Draw	1.9A@12V, 0.9A@24V	J. W/CIII	10.0kg	GetTite
30W	9	· ·	Die-cast Aluminum	CTN Size	42*35*31cm	
		Mouting Bracket				
	-	IP Rating	IP68	CTN Vol.	$0.046 \text{m}^3$	
		Life-span	50,000 Hours			

		D 0 1 1	G 771 1			
		Beam Optional	Spot/Flood	PCs/ctn	20pcs	
JT-4618		LED Chip	3W Epistar		•	
	22225	Power	18W	N.W/pc	0.70kg	
	25522	Lumen	1350LM		-	
6 inch		Working Voltage		G.W/ctn	14.5kg	<b>Get Price</b>
18W		Current Draw	1.4A@12V,0.7A@24V			
Forklift	COOOL MILES	· ·	Die-cast Aluminum	CTN Size	30*20*29cm	
Light	Δ, γ	Mouting Bracket				
HOT		IP Rating	IP68	CTN Vol.	$0.017m^{3}$	
		Life-span	50,000 Hours			
		Beam Optional LED Chip	Spot/Flood	PCs/ctn	20pcs	
JT-4918	THE REAL PROPERTY.	Power	3W Epistar 18W			
	S ACCES		1350LM	N.W/pc	0.70kg	
	S. C. C. C.	Lumen Working Voltage				
6.3 inch		Current Draw	1.4A@12V,0.7A@24V	G.W/ctn	12.0kg	<b>Get Price</b>
18W			Die-cast Aluminum			
10 **	CE.S	Mouting Bracket		CTN Size	50*44*22cm	
	T	IP Rating	IP68			
HOT		Life-span	50,000 Hours	CTN Vol.	$0.048 \text{m}^3$	
		Beam Optional	Spot/Combo			
		LED Chip	5W CREE	PCs/ctn	20pcs	
JT-4940		Power	40W			
	2016	Lumen	3200LM	N.W/pc	0.70kg	
	COSCOUNT	Working Voltage				
6 inch		Current Draw	2.0A@12V,1.4A@24V	G.W/ctn	15.0kg	<b>Get Price</b>
40W	0.0.0.0		Die-cast Aluminum			
Slim		Mouting Bracket		CTN Size	45x39x25cm	
		IP Rating	IP68			
HOT		Life-span	50,000 Hours	CTN Vol.	$0.044 \text{m}^3$	
		Beam Optional	Spot/Flood	DG /	•	
TT: 1015		LED Chip	3W Epistar	PCs/ctn	20pcs	
JT-1215	33333	Power	15W	NI XX//	0.601	
	CONTRACTOR IN	Lumen	1080LM	N.W/pc	0.60kg	
5.7 inch		Working Voltage	9-32V DC	C W/str	10.51-	Cat Daile
15W		Current Draw	0.9A@12V,0.5A@24V	G.W/ctn	12.3Kg	<b>Get Price</b>
Marine	100000	Housing Materials	Die-cast Aluminum	CTN Sizo	44*23*24cm	
Light		Mouting Bracket	Stainless Steel	CTIV SIZE	77 23 24CIII	
Black/		IP Rating	IP68	CTN Vol.	0.024m³	
White		Life-span	50,000 Hours	CII VOI.	0.02 <del>-1</del> 111	
		Beam Optional	Flood Beam	PCs/ctn	20pcs	
JT-3912	N=20	LED Chip	3W CREE	25,001	-0P-0	
	6	Power	12W	N.W/pc	0.60kg	
		Lumen	960 LM			
5.9 inch		Working Voltage		G.W/ctn	12.5kg	<b>Get Price</b>
12W	0	Current Draw	0.6A@12V, 0.3A@24V		0	
Marine		· ·	Die-cast Aluminum	CTN Size	37*34*28cm	
Light		Mouting Bracket				
		IP Rating	IP68	CTN Vol.	$0.035 \text{m}^3$	
		Life-span	50,000 Hours			

		Beam Optional	Spot Beam	PCs/ctn	20	
JT-4812		LED Chip	3W CREE	PCS/Ctn	20pcs	
J1-4012		Power	12W	N.W/pc	0.60kg	
	4 3 1	Lumen	1080LM	14. W/pc	0.00kg	
4.9 inch	All all	Working Voltage	9-32V DC	G.W/ctn	12.5kg	<b>Get Price</b>
12W		Current Draw	0.8A@12V,0.4A@24V	G. W/Cth	12.3Kg	Gerrice
Marine	0	_	Die-cast Aluminum	CTN Size	44*23*24cm	
Light		Mouting Bracket	Stainless Steel	CTIVBIZE	11 23 2 10111	
		IP Rating	IP68	CTN Vol.	$0.024 \text{m}^3$	
		Life-span	50,000 Hours			
		Beam Optional	Long Range Spot Beam	PCs/ctn	20pcs	
JT-1515		LED Chip	15W CREE COB		1	
		Power	15W	N.W/pc	0.60kg	
		Lumen	1080 LM	1	$\mathcal{E}$	
3.7 inch		Working Voltage		G.W/ctn	13.0kg	<b>Get Price</b>
15W		Current Draw	1.5A@12V,0.6A@24V			
Marine			Die-cast Aluminum	CTN Size	47*34*25cm	
Light		Mouting Bracket				
Long		IP Rating	IP68	CTN Vol.	$0.040 \text{m}^3$	
Range		Life-span	50,000 Hours			
		Beam Optional	Long Range Spot Beam	PCs/ctn	20pcs	
JT-1520		LED Chip Power	20W CREE COB 20W			
		Lumen	20W 1440LM	N.W/pc	0.85kg	
1 in ala		Working Voltage				
4 inch 20W		Current Draw	2.0A@12V,0.8A@24V	G.W/ctn	18.0kg	<b>Get Price</b>
Marine			Die-cast Aluminum			
Light		Mouting Bracket		CTN Size	47*34*25cm	
Long	1	IP Rating	IP68			
Range		Life-span	50,000 Hours	CTN Vol.	$0.040 \text{m}^3$	
		Beam Optional	Spot Beam			
		LED Chip	25W CREE COB	PCs/ctn	20pcs	
JT-1525		Power	25W			
		Lumen	1800LM	N.W/pc	1.00kg	
4 inch		Working Voltage	9-32V DC	G W	21.01	G (P)
25W		Current Draw	1.8A@12V,1.1A@24V	G.W/ctn	21.UKg	Get Price
Marine		Housing Materials	Die-cast Aluminum	CTN C:-	40*24*2F - · · ·	
Light		Mouting Bracket	Stainless Steel	CIN Size	48*34*25cm	
Long		IP Rating	IP68	CTN Vol.	0.041m3	
Range		Life-span	50,000 Hours	CIN VOI.	0.041111	
		Beam Optional	Flood Beam	PCs/ctn	20pcs	
JT-1524		LED Chip	3W Epistar	20,001	Lopes	
U 1 - 1347		Power	24W	N.W/pc	0.75kg	
		Lumen	1300 LM	, pc	5.70Mg	
		Working Voltage		G.W/ctn	16.0kg	<b>Get Price</b>
5.6 inch		Current Draw	1.5A@12V,0.8A@24V			22227760
24W			Die-cast Aluminum	CTN Size	37*34*28cm	
		Mouting Bracket				
		IP Rating	IP68	CTN Vol.	$0.035 \text{m}^3$	
		Life-span	50,000 Hours			

		Beam Optional	Spot/Flood	DC / /	10	
IT 1505		LED Chip	3W CREE	PCs/ctn	12pcs	
JT-1527		Power	27W	NI XXI/m o	1 001-	
		Lumen	2100LM	N.W/pc	1.00kg	
		Working Voltage	10-30V DC	G.W/ctn	12 Oka	Get Price
5.7 inch		Current Draw	1.8A@12V,0.8A@24V	G. W/CIII	13.0kg	GetTite
27W	D. C.	Housing Materials	Die-cast Aluminum	CTN Size	42*34*38cm	
		Mouting Bracket	Stainless Steel	CTIVBIZE	42 54 50cm	
		IP Rating	IP68	CTN Vol.	$0.054 \text{m}^3$	
		Life-span	50,000 Hours	0111 / 011		
		Beam Optional	Spot/Flood	PCs/ctn	12pcs	
JT-1536		LED Chip	3W CREE		•	
	E LEEEN	Power	36W	N.W/pc	1.50kg	
		Lumen	2700LM			
6 0 in ala		Working Voltage Current Draw		G.W/ctn	19.0kg	<b>Get Price</b>
6.9 inch 36W			2.4A@12V,1.1A@24V Die-cast Aluminum			
30 **		Mouting Bracket		CTN Size	50*34*42cm	
		IP Rating	IP68			
		Life-span	50,000 Hours	CTN Vol.	$0.071 \text{m}^3$	
		Beam Optional	Spot/Flood			
	1000	LED Chip	5W CREE	PCs/ctn	12pcs	
JT-1545	A RELIANT	Power	45W	N 1 1 1 1 1 /	N.W/pc 1.70kg	
		Lumen	3000 LM	N.W/pc 1.70kg		
		Working Voltage	9-32V DC	G.W/ctn	21 Oka	Get Price
5.5 inch		Current Draw	3.8A@12V,1.8A@24V	G. W/CIII	21.0kg	GetTite
45W		Housing Materials	Die-cast Aluminum	CTN Size	51*46*25cm	
		Mouting Bracket			01 10 200111	
		IP Rating	IP68	CTN Vol.	0.059m³	
	•	Life-span	50,000 Hours			
		Beam Optional	Spot/Flood 5W CREE	PCs/ctn	8pcs	
JT-1560		LED Chip Power	60W			
		Lumen	3500 LM	N.W/pc	2.40kg	
	66 6009	Working Voltage				
7 inch	200 B	Current Draw	5A@12V,2.5A@24V	G.W/ctn	20.0kg	<b>Get Price</b>
60W		Housing Materials	Die-cast Aluminum	GTD Y G	7.1.b.10.b.07	
		Mouting Bracket	Stainless Steel	CTN Size	54*42*27cm	
		IP Rating	IP68	CTN Vol.	0.0613	
		Life-span	50,000 Hours	CIN VOI.	0.0011119	
		Beam Optional	Spot/Flood	PCs/ctn	брсѕ	
JT-1265		LED Chip	3W CREE	2 05/0011	CP CS	
	560 8	Power	51W	N.W/pc	2.50kg	
	0000	Lumen	2900 LM	_ ^		
7 inch	0 000	Working Voltage		G.W/ctn	15.5kg	<b>Get Price</b>
51W Black/	000000	Current Draw	2.6A@12V,1.5A@24V			
Red		Mouting Bracket	Die-cast Aluminum	CTN Size	48*27*39cm	
	THE PARTY OF THE P	IP Rating	IP68			
Classic		Life-span	50,000 Hours	CTN Vol.	$0.051 \text{m}^3$	
		-iic spaii	20,000 110010	<u> </u>		

	_	Beam Optional	Spot/Flood			
		LED Chip	•	PCs/ctn	12pcs	
JT-1860	5/200	Power	5W Epistar 60W			
		Lumen	4800LM	N.W/pc	1.70kg	
	STATE OF THE	Working Voltage				
5 inch	0.0	Current Draw	4.2A@12V, 2.3A@24V	G.W/ctn	21.0kg	<b>Get Price</b>
60W	66		Die-cast Aluminum			
00 11	6 6	Mouting Bracket		CTN Size	51*46*25cm	
		IP Rating	IP68			
		Life-span	50,000 Hours	CTN Vol.	$0.059 \text{m}^3$	
		Beam Optional	High/Low Beam			
Angel		LED Chip	10W CREE	PCs/ctn	4pcs	
Eye		Power	60W			
<b>J</b>	3301	Lumen	4800 LM/2400LM	N.W/pc	1.40kg	
7 inch	000	Working Voltage				
60W		Plug	H4	G.W/ctn	7.8kg	<b>Get Price</b>
Jeep		C	Die-cast Aluminum	amy at	40.400.400	
Headlight		Mouting Bracket		CTN Size	48*29*28cm	
		IP Rating	IP68	CTN I I I	0.000	
		Life-span	50,000 Hours	CTN Vol.	$0.039 \mathrm{m}^3$	
		Beam Optional	High/Low Beam	DC / /	4	
Angel		LED Chip	10W/3W CREE	PCs/ctn	4pcs	
Eye 2		Power	70W/55W/3W	NI XX//	1 401-	
		Lumen	6020lm /4730lm /258lm	N.W/pc	1.40kg	
7 inch		Working Voltage	9-32V DC	C W/otro	7.01	C-4 D-3
73W		Plug	H4	G.W/ctn	7.8Kg	<b>Get Price</b>
Jeep		Housing Materials	Die-cast Aluminum	CTN Size	48*29*28cm	
Headlight		Mouting Bracket	Stainless Steel	CIN Size	40.73.790111	
		IP Rating	IP68	CTN Vol.	0.039m3	
		Life-span	50,000 Hours	CIIV VOI.	0.037111	
		Beam Optional	Spot Beam	PCs/ctn	20pcs	
JT-		LED Chip	10W CREE		2000	
FL0030		Power	30W	N.W/pc	0.75kg	
		Lumen	2400LM			
4 inch	t <sub>e</sub> i	Working Voltage		G.W/ctn	15.2kg	Get Price
30W		Plug	H4		S	
Fog Light		_	Die-cast Aluminum	CTN Size	33*28*62cm	
		Mouting Bracket				
<b>EMBED</b>		IP Rating	IP68	CTN Vol.	$0.057 \text{m}^3$	
		Life-span	50,000 Hours			
TO		Beam Optional	Spot Beam	PCs/ctn	20pcs	
JT-		LED Chip	10W CREE			
FL0030-1		Power	30W	N.W/pc	0.90kg	
	CE COLLEGE	Lumen	2400LM			
4 inch	- 11 ( = m ) ( )	Working Voltage	9-32V DC H4	G.W/ctn	19.0kg	<b>Get Price</b>
30W		Plug Housing Materials				
Fog Light		Mouting Bracket	Die-cast Aluminum	CTN Size	33*28*62cm	
	7 7	IP Rating	IP68			
<b>MOUNT</b>		Life-span	50,000 Hours	CTN Vol.	$0.057 \text{m}^3$	
		ruc-shan	50,000 H0uis			

Beam Optional Spot/I	IPCs/ctn	12pcs	
1.11-2850 1	CREE	•	
Power 50W	N.W/pc	1.30kg	
Lumen 5000I	LM	C	
Working Voltage 9-48V	IG.W/ctn	16.5kg	<b>Get Price</b>
	@12V,1.8A@24V	C	
50W Housing Materials Die-ca	ICTN S17	e 67*41*28cm	
C	ess Steel		
10W IP Rating IP68	CTN Vo	1. 0.077m³	
	0 Hours		
Beam Optional Spot I LED Chip 10W 0	IPCs/cfn	12pcs	
JT-2950   EED Chip   10W C	CKEE		
400	N.W/pc	1.50kg	
Lumen 4500I Working Voltage 10-30			
	©12V,1.9A@24V G.W/ctn	18.8kg	<b>Get Price</b>
50W Housing Materials Die-ca	· ·		
Mouting Bracket Stainl	ICTN S17	e 39*38*35cm	
10W IP Rating IP68			
	0 Hours	1. 0.052m <sup>3</sup>	
Beam Optional Spot/I	Flood		
LED Chin 10W (	CREE PCs/ctn	8pcs	
JT-2960 Power 60W		• • • • •	
Lumen 5400I	LM N.W/pc	2.80kg	
Working Voltage 10-30	V DC	24.51	C + D :
5.3 inch   Current Draw 5.2A@	@12V,2.3A@24V G. W/ctm	24.5kg	Get Price
60W Housing Materials Die-ca	ast Aluminum	e 43*38*36cm	
Mouting Bracket Stainl	ess Steel	æ 43.36.30cm	
IP Rating IP68	CTN Vo	1. 0.059m³	
Life-span 50,000	0 Hours	1. 0.037III	
Beam Optional Spot/I	IPCs/ctn	8pcs	
JT-2990 LED Chip 10W 0	CREE	or	
Power 90W	N.W/pc	2.80kg	
Lumen 8100I		C	
Working Voltage 10-30	I(†.W/ctn	24.5kg	<b>Get Price</b>
	@12V,3.2A@24V		
	ICTN S17	e 43*38*36cm	
Mouting Bracket Stainl IP Rating IP68	ess steet		
	O Hours CTN Vo	1. 0.059m³	
Beam Optional Spot/I			
JT-1210- LED Chip 10W 0	IPCs/ctn	8pcs	
80W Power 80W			
Lumen 6700 1	LM N.W/pc	2.20kg	
Working Voltage 9-60V	' DC	10.51	a · · ·
Current Draw 67A6	@12V,3.5A@24V G.W/ctn	18.5kg	Get Price
5.5 inch Housing Materials Die-ca	ast Aluminum	10*40*2C	
Mouting Bracket Stainl	ess Steel	e 49*40*26cm	
10W IP Rating IP 67	CTN V	1. 0.051m³	
CREE Life-span 50,000	0 Hours	1. U.UJ1III <sup>-</sup>	

		Beam Optional	Spot/Flood			
		LED Chip	5W CREE	PCs/ctn	4pcs	
JT-8100		Power	100W			
	THE WIND	Lumen	5000 LM	N.W/pc	3.80kg	
		Working Voltage				
6 inch		Current Draw	5.8A@12V,2.9A@24V	G.W/ctn	15.8kg	<b>Get Price</b>
100W			Die-cast Aluminum			
		Mouting Bracket		CTN Size	50*46*19cm	
		IP Rating	IP68			
		Life-span	50,000 Hours	CTN Vol.	$0.044 \text{m}^3$	
		Beam Optional	Spot/Flood	DG /		
TT 0120		LED Chip	10W CREE	PCs/ctn	4pcs	
JT-8120		Power	120W	NI XX//	2.051	
		Lumen	8450 LM	N.W/pc	3.95kg	
		Working Voltage	9-32V DC	C W/otro	16 61.0	C-4 D-3
7.4 inch		Current Draw	7A@12V,3.4A@24V	G.W/ctn	10.0Kg	Get Price
120W		Housing Materials	Die-cast Aluminum	CTN Size	50*46*19cm	
		Mouting Bracket	Stainless Steel	CIN Size	30°40° 19CIII	
TOUGH	777	IP Rating	IP68	CTN Vol.	0.044m3	
TOUGH		Life-span	50,000 Hours	CIN VOI.	0.044111	
		Beam Optional	Spot/Flood Cover	PCs/ctn	4pcs	
JT-1590-		LED Chip	5W CREE	1 CS/CtH	трез	
1		Power	90W	N.W/pc	4.00kg	
		Lumen	7740 LM	1 (. ( ) / pc	ong	
		Working Voltage		G.W/ctn	17.0kg	<b>Get Price</b>
7 inch		Current Draw	6.2A@12V,3.0A@24V			<u> </u>
90W		_	Die-cast Aluminum	CTN Size	50*26*41cm	
		Mouting Bracket				
NEW	8	IP Rating	IP68	CTN Vol.	$0.053 \text{m}^3$	
		Life-span	50,000 Hours			
		Beam Optional	Spot/Flood Cover	PCs/ctn	4pcs	
JT-15140		LED Chip Power	5W CREE			
	(1) 美文文学	Lumen	140W 12000 LM	N.W/pc	4.00kg	
	· 10 - 10 - 10 - 10 - 10 - 10 - 10 - 10	Working Voltage				
7 inch	之名为军局	Current Draw	9.4A@12V, 4.8A@24V	G.W/ctn	17.0kg	<b>Get Price</b>
140W	124 FF		Die-cast Aluminum			
	S 25 35 0	Mouting Bracket		CTN Size	50*26*41cm	
		IP Rating	IP68			
NEW		Life-span	50,000 Hours	CTN Vol.	$0.053 \text{m}^3$	
	•	Beam Optional	Spot/Flood Cover			
VT 4 50 6	184.400	LED Chip	3W CREE	PCs/ctn	4pcs	
JT-1596	2 1 6 6 6 6 6	Power	96W	N	4 0.01	
	· Preserve	Lumen	8600LM	N.W/pc	4.00kg	
	000000	Working Voltage	9-60V DC	C W/st=	17 Olac	Cot D
9 inch		Current Draw	6.4A@12V,3.3A@24V	G.W/ctn	1 / .UKg	Get Price
96W	Control of the second	Housing Materials	Die-cast Aluminum	CTM C:	50*24*20~	
	FT :	Mouting Bracket	Stainless Steel	CIN Size	52*34*32cm	
NEW		IP Rating	IP68	CTN Vol.	0.057m3	
TAE VV		Life-span	50,000 Hours	CIN VOI.	0.03/111	

		Beam Optional	Spot Beam	PCs/ctn	4pcs	
JT-15120	A CO	LED Chip	5W CREE		•	
01 10120	6 6 6 6 6	Power	120W	N.W/pc	4.00kg	
	0000	Lumen	10000LM	14. W/pc	4.00Kg	
	10000000000000000000000000000000000000	Working Voltage	9-60V DC	G.W/ctn	17 Oka	<b>Get Price</b>
9 inch	· · · FAREE	Current Draw	7.9A@12V,4.3A@24V	G. W/CIII	17.0kg	GetTite
120W	A SIGNET	Housing Materials	Die-cast Aluminum	CTN Size	52*34*32cm	
	607	Mouting Bracket	Stainless Steel	CIN Size	32 · 34 · 32CIII	
		IP Rating	IP68	CTN Vol.	0.057-3	
	0	Life-span	50,000 Hours	CIN VOI.	0.03/1119	
		Beam Optional	Spot/Flood Cover	PCs/ctn	Anas	
JT-	juntuseia	LED Chip	5W CREE	PCs/ctn 4pcs	4pcs	
15185-1		Power	185W	N.W/pc	4.00kg	
		Lumen	17500 LM	14. W/pc	4.00kg	
		Working Voltage	9-32V DC	G.W/ctn	17 Oka	Cot Dries
9 inch		Current Draw	12.9A@12v,7.9A@24v	G. W/CIII	17.0kg	Get Price
225W		Housing Materials	Die-cast Aluminum	CTN Sizo	52*34*32cm	
		Mouting Bracket	Stainless Steel	CIN Size	32 · 34 · 32CIII	
	YEAR Minary Connector	IP Rating	IP68	CTN Vol.	0.057m3	
	NEW 9inch 225W CREE	Life-span	50,000 Hours	CIN VOI.	0.03/111	

- 1. MOQ: One CTN(Carton)/Model, Price Term: EXW Factory without Delivery or FOB Charges;
- 2. Payment Method: TT/Paypal/Western Union/Escrow (Transfer charge paid by buyer side);
- 3. Packing: Plain white box without logo, Custom Logo can be engraved per your request;
- 4. Delivery: 1-7 days for samples; 7-30 days for bulk production;
- 5. One year warranty and life-long after-sale services provided;
- 6. Quote valid date: 30 days since this quotation received.



## Juntu West Guangzhou Juntu Auto Accessories Co., Ltd.

Email: sales7@juntu-auto.com Mob/Whatsapp: +8615899973510 Contact: Mike Zheng

Skype: Sales7-mike Facebook/Wechat: mike652638 Website: www.juntu-auto.com

### **Product List for LED Warning & Signal Lights**

Model	Picture for Reference Contact Mike for More Pictures	Spe	ecification	Pacl	king Details	Get Price Via Email Inquiry
JT-	0000	Color Options LED Type	Amber/Red/White 3mm High Flux	Sets/ctn	40sets	
SML001		Working Voltage Power	9-18V DC 0.15W/pc	N.W/set	0.20kg	
0.79 inch		Package Size per Light	10pcs/set 29*20*27mm	G.W/ctn	9.0kg	<b>Get Price</b>
0.15W 10pcs/set		Hole Diameter Wire Length	20mm (0.79inch) 20cm (7.9inch)	CTN Size	38*35*33cm	
NEW		IP Rating Life Span	IP68 Waterproof Over 15,000 hours	CTN Vol.	$0.044 \text{m}^3$	
JT-	LED Singnal Lights/Strobe Function	Color Options Beam Options	Amber/Red/White Spot/Flood	Sets/ctn	20sets	
SL4012		LED Chip Working Voltage	CREE 12-30V DC	N.W/set	0.65kg	
5.7 inch	us rate of the little of the l	Power Lumen	4*3W 1200 LM	G.W/ctn	14.0kg	<b>Get Price</b>
12W 2pcs/set		Housing Materials Mouting Bracket	Die-cast Aluminum Stainless Steel	CTN Size	66*37*18cm	
NEW	2[]CS 5.7(nch 12W 1200 LW	IP Rating Life Span	IP68 Waterproof Over 50,000 hours	CTN Vol.	0.044m³	
JT-	and the second s	Color Strobe Modes	Amber 6 Modes	PCs/ctn		
WL001		LED Chip Working Voltage	High Flux LEDs 9-32V DC	N.W/pc	1.20kg	
10.8 inch	@>	Power Lumen	40*0.5W 1850LM	G.W/ctn		<b>Get Price</b>
20W		Product Size Mouting Method	10.8*6.1*1.6 inches Magnetic Base	CTN Size		
NEW		IP Rating Life Span	IP68 Waterproof Over 50,000 hours	CTN Vol.		

- 1. MOQ: One CTN(Carton)/Model, Price Term: EXW Factory without Delivery or FOB Charges;
- 2. Payment Method: TT/Paypal/Western Union/Escrow (Transfer charge paid by buyer side);
- 3. Packing: Plain white box without logo, Custom Logo can be engraved per your request;
- 4. Delivery: 1-7 days for samples; 7-30 days for bulk production;
- 5. One year warranty and life-long after-sale services provided;
- 6. Quote valid date: 30 days since this quotation received.



# Juntu See Guangzhou Juntu Auto Accessories Co., Ltd.

Contact: Mike Zheng Email: sales7@juntu-auto.com Mob/Whatsapp: +8615899973510

Skype: Sales7-mike Facebook/Wechat: mike652638 Website: www.juntu-auto.com

## **Product List for Mounting Brackets**

Model	Picture for Reference Contact Mike for More Pictures	Specification	Packing Details	Get Price Via Email Inquiry
ZJ-001	The second secon	Circle Size: 1.25inch (32mm) Color: Black/ Silver Material: Aluminum Stainless Steel Screws Included Coating: Spraying/Anodic Oxidation Application: Universal on Offroad Vehicles, SUV, Truck, Jeep, Pick-up, etc.	Sets/CTN 50sets  N.W/set 0.25kg  G.W/ctn 13.0kg  CTN Size 47*31*32cm  CTN Vol. 0.047m³	Get Price
ZJ-001A	M6 M8	Circle Size: 1.5inch (38mm) Color: Black/ Silver Material: Aluminum Stainless Steel Screws Included Coating: Spraying/Anodic Oxidation Application: Universal on Offroad Vehicles, SUV, Truck, Jeep, Pick-up, etc.	Sets/CTN 50sets  N.W/set 0.26kg  G.W/ctn 14.0kg  CTN Size 47*31*32cm  CTN Vol. 0.047m³	Get Price
ZJ-002	2PCS  Stroil Plinch(Mann)	Circle Size: 1.73inch (44mm) Color: Black/ Silver Material: Aluminum Stainless Steel Screws Included Coating: Spraying/Anodic Oxidation Application: Universal on Offroad Vehicles, SUV, Truck, Jeep, Pick-up, etc.	Sets/CTN 50sets  N.W/set 0.28kg  G.W/ctn 15.0kg  CTN Size 47*31*32cm  CTN Vol. 0.047m³	Get Price
ZJ-003	SIZE: ZINCH (S1MM)	Circle Size: 2.0inch (51mm) Color: Black/ Silver Material: Aluminum Stainless Steel Screws Included Coating: Spraying/Anodic Oxidation Application: Universal on Offroad Vehicles, SUV, Truck, Jeep, Pick-up, etc.	Sets/CTN 50sets  N.W/set 0.29kg  G.W/ctn 16.0kg  CTN Size 47*31*32cm  CTN Vol. 0.047m³	Get Price

ZJ-003A	Size:2.5inch(64mm)  2PCS	Circle Size: 2.5inch (64mm) Color: Black/ Silver Material: Aluminum Stainless Steel Screws Included Coating: Spraying/Anodic Oxidation Application: Universal on Offroad Vehicles, SUV, Truck, Jeep, Pick-up, etc.	Sets/CTN N.W/set G.W/ctn CTN Size CTN Vol.	0.30kg 16.0kg 47*31*32cm	Get Price
ZJ-004	2PCS	Circle Size: 3.0inch (76mm) Color: Black/ Silver Material: Aluminum Stainless Steel Screws Included Coating: Spraying/Anodic Oxidation Application: Universal on Offroad Vehicles, SUV, Truck, Jeep, Pick-up, etc.	Sets/CTN N.W/set G.W/ctn CTN Size CTN Vol.	0.31kg 13.0kg 47*31*46cm	Get Price
ZJ-005-1	2 pcs  thick thin  thin  Thick Liner Diameter: 19 mm  Thin Liner Diameter: 25 mm	Circle Size: 1.18inch (30mm) without Liner 1.0inch(25mm) with Thin Liner 0.75inch(19mm) with Thick Liner Color: Black/ Silver Material: Aluminum Stainless Steel Screws Included Coating: Spraying/Anodic Oxidation Application: Universal on Offroad Vehicles, SUV, Truck, Jeep, Pick-up, etc.	Sets/CTN N.W/set G.W/ctn CTN Size CTN Vol.	0.26kg 14.0kg 47*31*32cm	Get Price
ZJ-006-1	2PCS	Circle Size: 2inch (52mm) without Liner 1.5inch(38mm) with Thin Liner 1.0inch(25mm) with Thick Liner Color: Black/ Silver Material: Aluminum Stainless Steel Screws Included Coating: Spraying/Anodic Oxidation Application: Universal on Offroad Vehicles, SUV, Truck, Jeep, Pick-up, etc.	Sets/CTN N.W/set G.W/ctn CTN Size CTN Vol.	0.44kg 23.0kg 47*31*32cm	Get Price
ZJ-007	2 pcs  2 pcs  2 pcs  2 year warranty  49 m m - 54 m m	Circle Size: 2.13inch (54mm) Color: Black/ Silver Material: Aluminum Stainless Steel Screws Included Coating: Spraying/Anodic Oxidation Application: Universal on Offroad Vehicles, SUV, Truck, Jeep, Pick-up, etc.	Sets/CTN N.W/set G.W/ctn CTN Size CTN Vol.	0.46kg 24.0kg 47*31*32cm	Get Price

	~**		Sets/CTN	40sets	
ZJ-008	2PCS	Circle Size: 2.6inch (66mm) Color: Black/ Silver Material : Aluminum Stainless Steel Screws Included	N.W/set G.W/ctn	Č	Get Price
		Coating: Spraying/Anodic Oxidation Application: Universal on Offroad Vehicles, SUV, Truck, Jeep, Pick-up, etc.	CTN Size	47*31*46cm	
	Size-2.6" /65mm	venicles, 50 v, 11uck, Jeep, Fick-up, etc.	CTN Vol.	0.067m³	
	juntuve		Sets/CTN	40sets	
	Wind pale doll con	Circle Size: 3.3inch (83mm) Color: Black/ Silver	N.W/set	0.65kg	
ZJ-009	nati	Material : Aluminum Stainless Steel Screws Included Coating: Spraying/Anodic Oxidation	G.W/ctn	27.0kg	<b>Get Price</b>
		Application: Universal on Offroad Vehicles, SUV, Truck, Jeep, Pick-up, etc.	CTN Size	47*31*46cm	
	Size:3.5 /Bloom 2PCS		CTN Vol.	0.067m³	
	A-PILLAR HINGE MOUNTING BRACKET	G 1 - D1 - 1 / G'1	Sets/CTN	40sets	
			N.W/set	0.65kg	
ZJ-010	200	Stainless Steel Screws Included Coating: Spraying/Anodic Oxidation	G.W/ctn	27.0kg	Get Price
		Application: To fix Pod Lights on 2007- 2015 Jeep Wrangler JK	CTN Size	47*31*46cm	
			CTN Vol.	0.067m³	
	290mm/11.4* 70mm/2.5		Pcs/CTN	20sets	
	220mm/8.7 160mm/3.8* 120mm/4.7 20mm/08* <sub>ED</sub>	Car License Plate Frame Color: Black/ Silver	N.W/set	1.0kg/pc	
ZJ-011	370mm/14.8°	Material : Aluminum Stainless Steel Screws Included Coating: Spraying/Anodic Oxidation	G.W/ctn	21.0kg	Get Price
		Application: Universal on Offroad Vehicles, SUV, Truck, Jeep, Pick-up, etc.	CTN Size	79*33*44cm	
			CTN Vol.	0.115m³	
			Sets/CTN	8sets	
	PR	Color: Black	N.W/set	2.80kg	
ZJ-201	<b>6</b>	Material : Iron Coating: Spraying Application: To fix 50" Straight Led Light	G.W/ctn	24.0kg	<b>Get Price</b>
		Application: To fix 50" Straight Led Light Bar on Ford Raptor F150	CTN Size	46*31*33cm	
	726		CTN Vol.	0.047m³	

	4		Sets/CTN	10sets	
		Color: Black Material : Iron Coating: Spraying	N.W/set	1.40kg	
ZJ-202		Application: To Fix 50" Curved Led Light Bar on 2009-	G.W/ctn	16.0kg	<b>Get Price</b>
		2014 Dodge Ram 1500 2010-2014 Dodge Ram 2500/3500	CTN Size	79*33*44cm	
			CTN Vol.	0.115m³	
			Sets/CTN	10sets	
	I SI	Color: Black Material: Iron	N.W/set	1.40kg	
ZJ-203	9	Coating: Spraying Application: To fix 50" Straight Led Light Bar on Ford	G.W/ctn	16.0kg	Get Price
	TO TO	F150 (2009-2014) Ford F150 SVT Raptor (2010-2014)	CTN Size	79*33*44cm	
			CTN Vol.	0.115m <sup>3</sup>	
	2pcs		Sets/CTN	12sets	
		Color: Black Material : Iron	N.W/set	1.20kg	
ZJ-204	O O	Coating: Spraying Application: To Fix 50" Straight Led Light Bar on	G.W/ctn	15.0kg	Get Price
		2002-2008 Dodge Ram 1500/2500 & 2003- 2008 Dodge Ram 3500	CTN Size	64*35*23cm	
			CTN Vol.	0.052m³	
		Color: Black Material : Iron	Sets/CTN	12sets	
			N.W/set	2.30kg	
ZJ-205		Coating: Spraying Application: To Fix 4pcs of Pod/Fog	G.W/ctn	30.0kg	<b>Get Price</b>
		Lights OR 2pcs of Short Led Light Bars on Ford Raptor		64*35*23cm	
			CTN Vol.	0.052m³	
ZJ-206	Roof Mount Bracket		Pcs/CTN	12sets	
		Color: Black Material : Iron	N.W/set	0.70kg	
	2PCS	Coating: Spraying Application: To Fix 50" Curved Led Light	G.W/ctn	10.0kg	Get Price
		Bar on Dodge, Tanke and Jeep Grand Cherokee 1984-2001	CTN Size	64*35*23cm	
	FOR SOINCH CURVED LED LIGHT BAR		CTN Vol.	0.052m³	

ZJ-207	License Plate Mount Bracket Size:36cm X5.5cm X10.5cm	Color:Silver,Black Material:Aluminum Car License Plate Frame Coating: Spraying/Anodic Oxidation Application: Universal on Offroad Vehicles, SUV, Truck, Jeep, Pick-up, etc.	Pcs/CTN N.W/set G.W/ctn CTN Size CTN Vol.	0.90kg 12.0kg 73*43*24cm	Get Price
ZJ-208	ROOF STREET FOR 04-14 4wd Nissan Titan	Color: Black Material: Iron Coating: Spraying Application: 2004-2014 Nissan Titan 50" Curved Led light bar mounts	Pcs/CTN N.W/set G.W/ctn CTN Size CTN Vol.	0.70kg 10.0kg 64*35*23cm	Get Price
ZJ-209		Color: Black Material: Iron Coating: Spraying Application: To Fix 50inch Straight Led Light Bar on 2002-2008 Dodge Ram 1500 OR 2003-2009 Dodge Ram 2500/3500.	G.W/ctn	1.20kg 15.0kg 64*35*23cm	Get Price
ZJ-210	Portable Brackets with Strong Magnet Base	Portable Mounting Brackets with Strong Magnetic Base Color: Black Material: Iron Coating: Spraying Application: Universal on Offroad Vehicles, SUV, Truck, Jeep, Pick-up, etc, for Random Sizes of Led Bar/Work Lights	Pcs/CTN N.W/set G.W/ctn CTN Size CTN Vol.	1.20kg 15.0kg 64*35*23cm	Get Price
ZJ-301	A-Pillar Mounting Bracket To Fix 2pcs of 52" Curved Led Bar	Color: Black Material: Iron Coating: Spraying Application: To Fix 2 pcs of 52" Straight Led Light Bar on A Pillar of Jeep Wrangler 2006-2015	Sets/CTN N.W/set G.W/ctn CTN Size CTN Vol.	5.70kg 23.0kg 73*43*24cm	Get Price

	A-Pillar Mounting Bracket		G , /CITN, C	
ZJ-302	1pc 50/52" Straight Led Bar + 2 Pod Lights	Color: Black Material: Iron Coating: Spraying Application: To Fix 1 pc of 50"/52" Straight Led Light Bar + 2pcs of Pods on Jeep Wrangler 2006-2015	Sets/CTN 6sets  N.W/set 4.60kg  G.W/ctn 28.0kg  CTN Size 61*47*38cm  CTN Vol. 0.109m³	Get Price
ZJ-303	A-Pillar Mounting Bracket To Fix 1pc of 50/52" Straight Led Bar	Color: Black Material: Iron Coating: Spraying Application: To Fix 1 pc of 50"/52" Straight Led Light Bar on Jeep Wrangler 2006-2015	Sets/CTN 6sets  N.W/set 4.60kg  G.W/ctn 28.0kg  CTN Size 61*47*38cm  CTN Vol. 0.109m³	Get Price
ZJ-305		Hood Mounting Bracket Color: Black Material: Iron Coating: Spraying Application: To Fix 20-22inch LED Light Bar on 2007-2015 Jeep Wrangler JK	Sets/CTN 40sets  N.W/set 0.50kg  G.W/ctn 22.0kg  CTN Size 47*31*46cm  CTN Vol. 0.067m³	Get Price
ZJ-304	To Fix 2pcs of Pod Lights on A-Pillar of Jeep Wrangler	Color: Black Material: Iron Coating: Spraying Application: To Fix 2pcs of 2-3inch Pod Lights on Jeep Wrangler JK 2007-2015	Sets/CTN 50sets  N.W/set 0.30kg  G.W/ctn 16.0kg  CTN Size 47*31*32cm  CTN Vol. 0.047m³	Get Price
ZJ-306	To Fix 4pcs of Pod Lights on A-Pillar of Jeep Wrangler  Por 3inch Led Work Light FOR 07-15 Jeep Wrangler JK.	Color: Black Material: Iron Coating: Spraying Application: To Fix 4pcs of 2-3inch Pod Lights on Jeep Wrangler JK 2007-2015	Pcs/CTN 12sets  N.W/set 1.00kg  G.W/ctn 13.0kg  CTN Size 64*35*23cm  CTN Vol. 0.052m³	Get Price

ZJ-307	To Fix 4pcs of Pod Lights on A-Pillar of Jeep Wrangler	Color: Black Material: Iron Coating: Spraying Application: To Fix 4pcs of 2-3inch Pod Lights on Jeep Wrangler JK 2007-2015	G.W/ctn	0.90kg 11.0kg 64*35*23cm	Get Price
ZJ-309	To Fix 2pcs of Pod Lights on Bumper of Offroad Vehicles  2	X Clamp Mounting Brackets Color: Black Material: Iron Coating: Spraying Application: Universal on Offroad Vehicles, SUV, Truck, Jeep, Pick-up, etc, to Fix Pod Lights on Bumpers	G.W/ctn	0.90kg 11.0kg 64*35*23cm	Get Price

- 1. MOQ: One CTN(Carton)/Model, Price Term: EXW Factory without Delivery or FOB Charges;
- 2. Payment Method: TT/Paypal/Western Union/Escrow (Transfer charge paid by buyer side);
- 3. Packing: Plain white box without logo, Custom Logo can be engraved per your request;
- 4. Delivery: 1-7 days for samples; 7-30 days for bulk production;
- 5. One year warranty and life-long after-sale services provided;
- 6. Quote valid date: 30 days since this quotation received.



# Juntu See Guangzhou Juntu Auto Accessories Co., Ltd.

Contact: Mike Zheng Email: sales7@juntu-auto.com Mob/Whatsapp: +8615899973510

Skype: Sales7-mike Facebook/Wechat: mike652638 Website: www.juntu-auto.com

### **Product List for Wiring Kits & DT Connectors**

Model	Picture for Reference Contact Mike for More Pictures	Specification	Get Price Via Email Inquiry
DT- XBDX		DT 2 Pin Connector Kit IP Rating: IP68 AWG: 16-18 GA Net Wet: 0.02KG/pc Applicabe for Led Work Light (Bar) below 180W	Get Price
DT- DBDX		DT 2 Pin Connector Kit  IP Rating: IP68  AWG: 14-16 GA  Net Wet: 0.03KG/pc  Applicabe for Led Work Light (Bar) below 300W	Get Price
DT- 3PBDX		DT 3 Pin Connector Kit IP Rating: IP68 AWG: 16-20 GA Net Wet: 0.03KG/pc Applicabe for Led Work Light (Bar) below 180W	Get Price
DT-XDX	330mm/13.0" 210mm/8.3"	DT 2 Pin Connector Kit IP Rating: IP68 AWG: 16-18 GA Net Wet: 0.05KG/pc Applicabe for Led Work Light (Bar) below 180W	Get Price

DT-DDX	220mm/8.7" 335mm/13.2"	DT 2 Pin Connector Kit IP Rating: IP68 AWG: 14-16 GA Net Wet: 0.07KG/pc Applicabe for Led Work Light (Bar) below 300W	Get Price
KG-001	DT Connector Pack Wire	Wiring Harness with DT Connector/Weather Pack/ Naked Wire Ends (Optional) Wire Length: 3M IP Rating: IP68 Net Weight: 0.53KG/pc Applicabe for Led Work Light (Bar) below 200W One Wiring Kit can connect 1pc of Light (Bar)	Get Price
KG-002	DT Weather Pack Wire	Wiring Harness with DT Connector/Weather Pack/ Naked Wire Ends (Optional) Wire Length: 3M IP Rating: IP68 Net Weight: 0.55KG/pc Applicabe for Led Work Light (Bar) below 200W One Wiring Kit can connect 2pcs of Light (Bar)	Get Price
KG-003		Wiring Harness with Naked Wire Ends Wire Length: 3M IP Rating: IP68 Net Wet: 0.65KG/pc Applicabe for Led Light (Bar) below 400W One Wiring Kit can connect 1pc of Light (Bar)	Get Price
Remark			
		el, Price Term: EXW Factory without Delivery or FOB C	
2. Payme	nt Method: TT/Paypal/W	Vestern Union/Escrow (Transfer charge paid by buyer sid	le);

- 2. Payment Method: TT/Paypal/Western Union/Escrow (Transfer charge paid by buyer side);
- 3. Packing: Plain white box without logo, Custom Logo can be engraved per your request;
- 4. Delivery: 1-7 days for samples; 7-30 days for bulk production;
- 5. One year warranty and life-long after-sale services provided;
- 6. Quote valid date: 30 days since this quotation received.